

CERTIFICATE OF COMPLIANCE

Certificate Number 20170126-E490320
Report Reference E490320-20170123
Issue Date 2017-JANUARY-26

Issued to: RITTAL CORP
1 RITTAL PL
URBANA OH 43078-5003

**This is to certify that
representative samples of**

ENVIRONMENTAL-RATED ACCESSORIES FOR
ENCLOSURES

See Addendum Page for Models

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

UL 50, Enclosures for Electrical Equipment, Non-
Environmental Considerations
UL 50E Enclosures for Electrical Equipment, Environmental
Considerations
CSA C22.2 No. 94.1.15 Enclosures for Electrical
Equipment, Non-Environmental Considerations
CSA C22.2 No. 94.2-15 Enclosures for Electrical
Equipment, Environmental Considerations

Additional Information:

See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20170126-E490320
Report Reference E490320-20170123
Issue Date 2017-JANUARY-26

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.


Models:

Model WK, f/b xx, f/b yy, f/b C, suitable for Type 1, 2, 3, 3R, 3S, 4, 5, 12 and 12K applications, where xx can be 5-35 and yy can be 3-23.

Model WK, f/b xx, f/b yy, f/b 4 or 6, suitable for Type 1, 2, 3, 3R, 3RX, 3S, 3SX, 3X, 4, 4X, 5, 12 and 12K applications, where xx can be 5-35 and yy can be 3-23.

Model WKDH, f/b xx, f/b yy, f/b C, suitable for Type 1, 2, 3, 3R, 3S, 4, 5, 12 and 12K applications, where xx can be 12-36 and yy can be 12-24.

Model WKDH, f/b xx, f/b yy, f/b 4 or 6, suitable for Type 1, 2, 3, 3R, 3RX, 3S, 3SX, 3X, 4, 4X, 5, 12 and 12K applications, where xx can be 12-36 and yy can be 12-24.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

