Rittal – The System.

Faster – better – everywhere.

VX SE Floormount enclosure system



Rittal and EPLAN

Your benefits at a glance





1. Engineering

- Error-free, flexible processes throughout the entire value chain with the digital twin
- High-quality 3D data in the EPLAN Data Portal
- 3D-assisted design with EPLAN Pro Panel

2. Sourcing

- Error-free product configuration with the Rittal Configuration System
- Interfaces with EPLAN engineering tools
- Simple ordering and fast delivery of Rittal standard products

More productive – with digitalization and prototyping Faster – with online configurators More reliable – with our smart, global service Better – with Industry 4.0 and automation



3. Manufacturing

- Rittal's fully automated production processes help guarantee precision machining, population and wire assembly
- Straightforward wiring with EPLAN Smart Wiring
- All work stations can be linked together with the digital twin

4. Operations

- Minimized downtimes and efficient production with the Rittal Global Service
- Predictive maintenance via IoT linking of Rittal cooling units
- The cloud-based solution EPLAN eVIEW allows a cross-locational overview of all project data



FRIEDHELM LOH GROUP

 \gg





VX SE – the solution

Reap the benefits of the VX SE Floormount Enclosure for your project:

- Minimal ordering and assembly work, thanks to the solid side panels and roof
- Body produced from a single piece for maximum stability and torsional rigidity
- High protection category up to IP 55/NEMA 12/3R
- The smart enclosure design from a single piece to help ensure good EMC properties
- Internally fastened rear walls and solid base maintain a secure seal
- 7 standard sizes to accommodate most floor mount applications
- Accepts common VX SE system accessories



IT INFRASTRUCTURE

Extra Protection

Added full width drip shield provides additional protection for the upper door area and the door gasket and requires no enclosure modification

18

Reliable pre-fixing

6

The clip at the top of the mounting plate holds it in place during one-person assembly until the plate can be screwed into position. The mounting plate is depth-adjustable on a 25 mm pitch pattern without the need for tools.

Ease of placement

The printed pitch pattern allows components to be easily and quickly positioned on the mounting plate – no measuring required.

-

Digitalization

Fully automated incorporation into the production workflow is easy with the QR code, for seamless digital monitoring at every stage, from incoming materials right through to the finished product.



Flexible interior installation

Interior installation with regard to depth couldn't be simpler, thanks to punched sections with mounting flanges 17 x 73 mm.

Installation options

The continuous pattern of square punchings supports the use of base accessories to create more mounting options at all levels.

Mounting Panel Slide Rails Provide rigid support for full size mounting panel installation and can

mounting panel installation and can be used elsewhere with the enclosure as additional component support

Solid Base

The full size internally fastened solid base allows plenty of space for cable entry and come pre-punched to accept standard leg kits

Reliable engineering

Rittal's customers are aided throughout the automated production process and when working with virtual prototypes, by accessing a comprehensive selection of conversion and planning tools:

- EPLAN Pro Panel
- 2D/3D CAD data – ecl@ss Advanced
- Technical documentation

100

- Data for planners

Carbon steel

The three-stage surface treatment process guarantees maximum protection against corrosion and is resistant to mineral oils, lubricants, machining emulsions and most solvents.

High level of protection Solid side panels and roof. Eliminating the gaps between the roof, side panel and frame helps to prevent dirt deposits.



Y W Lang



Rittal's customers are aided throughout the automated production process and when working with virtual prototypes, by accessing a comprehensive selection of conversion and planning tools: – EPLAN Pro Panel

14 111

- 2D/3D CAD data
- ecl@ss Advanced
- Technical documentation
- Data for planners



Safety

With this smart design, the side panels, roof and enclosure frame are conductively connected, so that no additional earthing is required. When using Rittal climate control equipment and Rittal fan-and-filter units in the the rear panel, no additional earthing is required.

> Effective shielding Good EMC properties are realized due to the smart enclosure construction from one single piece.

Optional Flexibility

Bolt-on leg kit accessory can be quickly added during integration or on site in the field for safer transportation and easier configurations

Secure Mounting

Heavy guage leg kits provide a secure means to bolt down the complete floormount assembly

VX SE Floormount enclosure system, carbon steel



	Basic enclosure, carbon steel	Floorstand Kits		
	 Material and surface finish: Enclosure: Carbon steel, 1.5 mm, dipcoat-primed, powder-coated on the outside, textured paint Door: Carbon steel, 2 mm, dipcoat-primed, powder-coated, textured paint Rear panel: Carbon steel, 1.5 mm, dipcoat-primed, powder-coated on the outside, textured paint, internally fastened Mounting plate: Carbon steel, 3 mm, zinc-plated, passivated Goland plates: Carbon steel, 1.5 mm, zinc-plated, passivated Solid base plate pre-punched for leg kits Color: RAL 7035 Protection category IP to IEC 60 529: IP 55 Protection category to UL 50E: Type 12 (NEMA 12), 3R Supply includes: Enclosure, solid top and sides Installable full width drip shield Rear panel, internally fastened Lock: 3 mm double-bit 2 punched rails 18 x 39 mm 	Material and surface finish: - Carbon steel, 3.0 mm, Powder-coated Color: - Ral 7035 Supply includes: - 1 pair of floorstands - All Attachment hardware		
Height Width Depth Doors Rear panel	Model No.	Leg Kit No.		
1600 1200 300 1 one-piece	5860.600	9963.546		
1600 1200 400 1 one-piece	5861.600	9963.522		
1600 1200 500 1 one-piece	5862.600	9963.523		
1600 1600 400 1 two-piece	5863.600	9963.522		
1600 1600 500 1 two-piece	5864.600	9963.523		
1800 1800 400 1 two-piece	5866.600	9963.522		

5867.600

9963.523

500

1

two-piece

1800

1800

System accessories



Punched sections with mounting flanges, 23 x 73 mm

Flexible interior installation on a 25 mm pitch pattern. With the system punchings, cage nuts up to M8 can be used across three levels. This allows you to securely fasten your own components with metric screws.



Punched sections without mounting flanges 23 x 73 mm and mounting rails 23 x 23 mm

For fixing at variable intervals and individually to the inner mounting surface of the enclosure frame. When mounted, the punched sections and rails sit flush to the enclosure frame. Due to the additional mounting bracket, they can be used with a pre-installed mounting plate and can also be cut to any required length.





Partial mounting plate

The partial mounting plates create additional mounting surfaces at all places in the enclosure. Suitable for use as a component shelf or hinged.



Threaded block

The threaded block enables simple metric screw-fastening. It may be used on the enclosure section as well as on punched sections and rails with square 12.5 x 11 mm punchings.

System accessories



LED system light

Connection is just as straightforward as assembly. The rotating connectors allow user-friendly connection, even in tight spaces. The wide ranging power supply unit means that the light can be used anywhere in the world.





Cable conduit and cable conduit holder Allows crush-proof cable routing to moving parts such as doors or swing frames with minimal assembly work



Cable duct


Cable ducts are ideal for managing large volumes of cables inside the enclosure. Components are simply screw-fastened. The screw heads may be securely covered with an isolator cap for insulation purposes. Cable ducts for vertical extrusions may be fitted directly onto the enclosure section, to save space on the mounting plate.



Sealing frame, modular

For universal use on all surfaces and walls, for inserting pre-assembled cables with connectors. Can also be mounted onto 24-pole or 16-pole connector cut-outs.

System accessories



Punched sections with mounting flanges, 17 x 73 mm The punched section with mounting flange, 17 x 73 mm, allows completely flexible installation on the tubular door

frame, no machining required.




Wiring plan lectern

During maintenance work, the wiring plan lectern folds out easily to hold circuit diagrams and documents. The integral punchings provide temporary accommodation for tools.



Spacers

Spacer bolts allow a mounting level to be quickly and easily created at the correct distance, onto which a top hat rail or a contact hazard protection cover for built-in components can be easily installed in the door.



Tubular door frame

The all-round T-head punchings allow simple, fast attachment of cables with standard commercially available cable ties.



Door stay for escape routes

The door stay for escape routes guarantees convenience and safety. The enclosure door is securely locked into position for assembly work. In dangerous situations, the stay is released automatically under pressure, and by using 180° hinges, escape routes can be kept clear in both directions.



Climate control

When using Rittal climate control devices and Rittal fan-and-filter units on the rear panel, no additional earthing is required. With this smart design, the side panels, roof and enclosure frame are conductively connected, so that no additional earthing is required.



Ride-up roller Even the heaviest populated door is easily opened and closed with the ride-up roller.



Comfort handle

For retro-fitting lock systems such as profile half-cylinders or lock inserts. As the handle does not take up any swing space, due to its folding action, the door surface area available for installed equipment is maximized.











Leg Kits

Model No.
9963546
9963522
9963523

Base/plinth

1 Base/plinth corner piece with base/plinth trim panel, front and rear, 100 mm				
For enclosure width mm	Model No.			
1200	8640.007			
1600	8640.008			
1800	8640.009			
2 Base/plinth trim panels, side, 1	00 mm			
For enclosure depth mm	Model No.			
300	8640.030			
400	8640.031			
500	8640.032			
3 Base/plinth corner piece with the front and rear, 200 mm	base/plinth trim panel,			
For enclosure width mm	Model No.			
1200	8640.025			
1600	8640.026			
1800	8640.027			
4 Base/plinth trim panels, side, 200 mm				
For enclosure depth mm	Model No.			
300	8640.040			
400	8640.041			
500	8640.042			







Doors/locks

1 Comfort handle For Model No. Lock inserts, RAL 7035 8611.020 Lock inserts, matt, chrome-plated 8611.330 Lock inserts and padlock, RAL 7035 8611.290 Profile half-cylinders, RAL 7035 8611.070 Profile half-cylinders, matt, chrome-plated 8611.340 2 180° hinges Color Model No. RAL 7035 8800.190 **2** 180° hinge for doors with high dynamic loads Color Model No. RAL 7035 8800.710

 Punched section with mounting f 	ange, 17 x 73 mm
For door width mm	Model No.
600	8612.050
800	8612.070
900	8612.080
Carbon steel wiring plan pocket,	depth 90 mm
For door width mm	Model No.
600	4116.000
800	4118.000
900	4123.000
3 Utility lectern	
For door width mm	Model No.
600	4638.600
800	4638.800
Door stay	
For all VX SE	Model No.
enclosures	4583.000
Door stay for escape routes	
For all VX SE	Model No.
enclosures	4583.500
Ride-up roller	
For all VX SE	Model No.
enclosures	4538.000
7 Wiring plan lectern	
For door width mm	Model No.
600 ¹⁾	4120.000
800 ¹⁾	4120.000
3 Support strip	
For door width mm	Model No.
600	4596.000
800	4598.000
1000	4599.000

Installation accessories for doors






















Cable management

1 Cable clamp rail, right-angle section				
For enclosure width mm Model No.				
1200	8619.440			
1600	8619.450			
1800	8619.460			
2 Sealing frame, modular ¹⁾				
	Model No.			
For all VX SE free-standing enclosures	2583.100 for 24-pole cut-out			
	2583.080 for 16-pole cut-out			

¹⁾ Also required: Seal inserts and inlays



Cable duct



Cable conduit



Cable conduit holder



Cable ties


Interior installation

C-rail 30/15, for direct installation	
For enclosure width/depth mm	Model No.
600	4944.000
800	4945.000
1000	4946.000
1200	4947.000
Punched section with mounting for the outer mounting level for i	
For enclosure width/depth mm	Model No.
300	8612.130
400	8612.140
500	8612.150
Punched section with mounting for the inner mounting level for i	flange 17 x 73 mm nstallation in the depth
For enclosure width/depth mm	Model No.
300	8612.030
400	8612.040
500	8612.050
600	8612.060
Punched section with mounting for installation in the depth	flange 23 x 73 mm
or enclosure width/height/depth mm	Model No.
500	8612.550
600	8612.560
800	8612.580
1000	8612.500
1200	8612.520
Punched section without mounti	ing flange 23 x 73 mm ¹⁾
or enclosure width/height/depth mm	Model No.
400	4374.000
500	4375.000
600	4376.000
800	4344.000
1000	4382.000
1200	4378.000
1800	4379.000
2000	4380.000
Punched rail 23 x 23 mm ²⁾	
or enclosure width/height/depth mm	Model No.
400	4169.000
500	4170.000
600	4171.000
800	4172.000
1000	4173.000
1200	4174.000
1400	4393.000
1600	41/5.000
1600 1800	4175.000 4176.000

annen 1









4

 ¹⁾ Also required:
 – Support bracket 8800.330 for mounting on the vertical section or
 – Support bracket 4183.000 for mounting on punched sections without mounting flanges or on punched rails


²⁾ Also required:

Mounting bracket 8800.370 for mounting on the vertical section or
 Mounting bracket 4182.000 for mounting on the bottom of the enclosure

section and at the top in the depth or on punched sections – U nut M4/M5/M6/M8







Interior installation

Support strip	
For enclosure width/depth mm	Model No.
Inner leve	el
400	4309.000
500	4596.000
600	8800.130
800	4579.000
Outer lev	el
400	4694.000
500	4695.000
600	4696.600
800	4697.000
Support rail 75 x 20 mm	
For enclosure width/depth mm	Model No.
slotted	
400	4394.000
500	4395.000
600	4396.000
800	4398.000
unslotted	k
600	4396.500
800	4398,500

9 Partial mounting plate

For installation in											
Enclosure width mm			Enclosure depth (side) mm			Door width mm	Dimensions mm	Model No.			
400	600	800	1000	1200	400	500	600	800			
		-	-	-		-		-	600	500 x 300	8614.640
-		-	-	-	-			-	600	500 x 400	8614.650
-	-	-	-	-	-	-	-	-	600	500 x 500	8614.660
-			-	-	-	-			600	500 x 700	8614.680
-		-	-	-	-	-		-	600	500 x 775	8614.675 ¹⁾
	-		-	-		-	-		800	700 x 300	8614.840
-	-	-	-	-	-		-	-	800	700 x 400	8614.850
-	-		-	-	-	-	-		800	700 x 700	8614.880
	-	-		-		-	-	-	1000	900 x 300	8614.040
-	-	-		-	-		-	-	1000	900 x 400	8614.050
-	-	-		-	-	-	-	-	1000	900 x 500	8614.060
	-	-	-			-	-	-	-	1100 x 300	8614.240
_	-	-	-	•	-	-	-	-	-	1100 x 400	8614.250
-		-	-		-	-		-	-	1100 x 500	8614.260

LED system light

1 LED system light ¹⁾					
Lumen Im	Version	Model No.			
900	without socket	2500.200			
900	without socket, 24 V (DC)	2500.220			
1200	with motion detector	2500.300			
1200	with motion detector, 24 V (DC)	2500.320			

¹⁾ Also required: – Connection accessories

Socket box

1 Socket box for LED system light ¹⁾					
	Socket	UL	Model No.		
	D, earthing-pin	-	2500.710		
	GB	_	2500.711		
•••	F/B	_	2500.712		
	СН	_	2500.713		
	US		2500.714		
	CN	-	2500.715		





) Also required: – Connection accessories



Spacers



Levelling feet



RiLine Busbar



Climate control

Flexible manufacturing

VX SE Floormount enclosures can be machined directly at the Rittal factory.

Use your own engineering data and order the enclosures with cut-outs e.g. for cooling units, fan-and-filter units or gland plates. In this way, you can boost the efficiency of your own manufacturing process.



Versatile solutions

The VX SE Floormount enclosure system is versatile, just like our clients. For your projects in different sectors, take advantage of all the benefits of the VX SE such as high protection categories, a wide range of sizes from 300 mm depth to 1800 mm width, different material options, simple and complete engineering and a comprehensive range of accessories.



Machine and plant engineering

With its high level of torsional rigidity, the VX SE is particularly well-suited to cope with dynamic loads and stresses when used with mobile lifting and operating equipment in a production plant or warehouse.



Building services (heating, climate control, ventilation)

With depths of 300 mm, the VX SE is the tailor-made solution where space is limited. Accessories such as the 180° hinge and the door stay make it easy to keep escape routes clear.

......

......

Rittal – The System.

Faster - better - everywhere.

- Enclosures
- Power Distribution
- Climate Control
- IT Infrastructure
- Software & Services

Rittal North America LLC Woodfield Corporate Center 425 North Martingale Road, Suite 400 • Schaumburg, Illinois 60173 • USA Phone: 937-399-0500 • Toll-free: 800-477-4000 Email: rittal@rittal.us • Online: www.rittal.com

Rittal Limited

6485 Ordan Drive • Mississauga, Ontario L5T 1X2 • Canada Phone: 905-795-0777 • Toll-free: 800-399-0748 E-Mail: marketing@rittal.ca • Online: www.rittal.ca



POWER DISTRIBUTION >> CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES



US994-BR-TR-10/23

FRIEDHELM LOH GROUP