

Safety data sheet

according to UK REACH



Printing date 01.09.2026

Version number 22 (replaces version 21)

Revision: 01.09.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Rittal Lackstift**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
RITTAL GmbH & Co.KG
Auf dem Stützelberg
D-35745 Herborn
Phone: +49 2772 505 0
e-mail: info@rittal.de
- **1.4 Emergency telephone number:**
Informationszentrale gegen Vergiftungen Bonn
Tel.: +49 228/19240 (emergency)
+49 228/287-3-3480 (office)
Fax: +49 228/287-3-3278

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms** GHS02, GHS07, GHS08
- **Signal word** Warning
- **Hazard-determining components of labelling:**
Reaction mass of ethylbenzene and xylene

(Contd. on page 2)

GB

Safety data sheet

according to UK REACH



Printing date 01.09.2026

Version number 22 (replaces version 21)

Revision: 01.09.2026

Trade name: Rittal Lackstift

(Contd. of page 1)

Hydrocarbons, C9, aromatics

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable

vPvB: Not applicable

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

EC number: 905-588-0 Reg.nr.: 01-2119488216-32	Reaction mass of ethylbenzene and xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	50-100%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	5-<10%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336, EUH066	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	<2.5%
CAS: 1675-54-3 EINECS: 216-823-5 Reg.nr.: 01-2119456619-26	Bis[4-(2,3-epoxypropoxy)phenyl]propane ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	≥0.25-<1%

(Contd. on page 3)

Safety data sheet

according to UK REACH



Printing date 01.09.2026

Version number 22 (replaces version 21)

Revision: 01.09.2026

Trade name: Rittal Lackstift

(Contd. of page 2)

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

GB

Safety data sheet

according to UK REACH



Printing date 01.09.2026

Version number 22 (replaces version 21)

Revision: 01.09.2026

Trade name: Rittal Lackstift

(Contd. of page 3)

Prevent formation of aerosols.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.· **Information about storage in one common storage facility:** Store away from foodstuffs.· **Further information about storage conditions:** Keep container tightly sealed.· **Storage class:** 3· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

Reaction mass of ethylbenzene and xylene

WEL Short-term value: 441 mg/m³, 100 ppm
 Long-term value: 220 mg/m³, 50 ppm
 Sk; BMGV

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
 Long-term value: 724 mg/m³, 150 ppm

108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm
 Long-term value: 274 mg/m³, 50 ppm
 Sk

· **DNELs**

Reaction mass of ethylbenzene and xylene

Dermal DNEL 212 mg/kg (Arbeiter)

Inhalative DNEL 221 mg/m³ (Arbeiter)

123-86-4 n-Butyl acetate

Dermal DNEL 6 mg/kg (general population)

11 mg/kg (Arbeiter)

Inhalative DNEL 300 mg/m³ (general population)

600 mg/m³ (Arbeiter)

· **Ingredients with biological limit values:**

Reaction mass of ethylbenzene and xylene

BMGV 650 mmol/mol creatinine
 Medium: urine
 Sampling time: post shift
 Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

(Contd. on page 5)

Safety data sheet

according to UK REACH



Printing date 01.09.2026

Version number 22 (replaces version 21)

Revision: 01.09.2026

Trade name: Rittal Lackstift

(Contd. of page 4)

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Hand protection**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

PVA gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Breakthrough time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Liquid

· **Colour:**

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined

· **Melting point/freezing point:**

Undetermined

· **Boiling point or initial boiling point and boiling range**

124-128 °C (123-86-4 n-Butyl acetate)

· **Flammability**

Flammable.

(Contd. on page 6)

GB

Safety data sheet

according to UK REACH

Printing date 01.09.2026

Version number 22 (replaces version 21)

Revision: 01.09.2026

Trade name: Rittal Lackstift

(Contd. of page 5)

· Lower and upper explosion limit	
· Lower:	1 Vol % (Reaction mass of ethylbenzene and xylene)
· Upper:	7 Vol % (Reaction mass of ethylbenzene and xylene)
· Flash point:	24 °C (DIN EN ISO 1523:2002, 1330-20-7 Xylene)
· Auto-ignition temperature:	390 °C (DIN 51794, 123-86-4 n-Butyl acetate)
· Decomposition temperature:	Not determined
· pH	Not determined
· Viscosity:	
· Kinematic viscosity at 20 °C	80-100 s (DIN 53211/4)
· Dynamic:	Not determined
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined
· Vapour pressure at 20 °C:	10.7 hPa (123-86-4 n-Butyl acetate)
· Vapour pressure at 50 °C:	55 hPa
· Density and/or relative density	
· Density at 20 °C:	1.092 g/cm ³ (DIN EN ISO 2811-1)
· Relative density	Not determined
· Vapour density	Not determined

9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· VOC (EC)	72.62 %
· Solids content (weight-%):	27.4 %
· Change in condition	
· Evaporation rate	Not determined

Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void

(Contd. on page 7)

Safety data sheet

according to UK REACH

Printing date 01.09.2026

Version number 22 (replaces version 21)

Revision: 01.09.2026

Trade name: Rittal Lackstift

(Contd. of page 6)

- | | |
|--|------|
| · Substances and mixtures, which emit flammable gases in contact with water | Void |
| · Oxidising liquids | Void |
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Possible in traces.
Nitrogen oxides
Hydrogen chloride (HCl)
Carbon monoxide
Nitrogen oxides (NO_x)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

Reaction mass of ethylbenzene and xylene

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	12,126 mg/kg (rabbit)
Inhalative	LC50/4 h	17.6 mg/l (rat)

123-86-4 n-Butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)

64742-95-6 Hydrocarbons, C9, aromatics

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

108-65-6 2-Methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **STOT-single exposure** May cause respiratory irritation.

(Contd. on page 8)

GB

Safety data sheet

according to UK REACH

Printing date 01.09.2026

Version number 22 (replaces version 21)

Revision: 01.09.2026

Trade name: Rittal Lackstift

(Contd. of page 7)

- **STOT-repeated exposure**
May cause damage to the hearing organs through prolonged or repeated exposure.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable
- **vPvB:** Not applicable
- **12.6 Endocrine disrupting properties**
For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) : hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

- | | |
|---------------------------------------|---|
| · 14.1 UN number or ID number | |
| · ADR/RID/ADN, IMDG, IATA | UN1263 |
| · 14.2 UN proper shipping name | |
| · ADR/RID/ADN | UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS |
| · IMDG | PAINT (Solvent naphtha), MARINE POLLUTANT |
| · IATA | PAINT |

(Contd. on page 9)

Safety data sheet

according to UK REACH

Printing date 01.09.2026

Version number 22 (replaces version 21)

Revision: 01.09.2026

Trade name: Rittal Lackstift

(Contd. of page 8)

· 14.3 Transport hazard class(es)

· ADR/RID/ADN



· Class 3 (F1) Flammable liquids.
· Label 3

· IMDG



· Class 3 Flammable liquids.
· Label 3

· IATA



· Class 3 Flammable liquids.
· Label 3

· 14.4 Packing group

· ADR/RID/ADN, IMDG, IATA III

· 14.5 Environmental hazards:

Product contains environmentally hazardous substances: Solvent naphtha

· Marine pollutant: Symbol (fish and tree)

· Special marking (ADR/RID/ADN): Symbol (fish and tree)

· 14.6 Special precautions for user

Warning: Flammable liquids.

· Hazard identification number (Kemler code): 30

· EMS Number: F-E, S-E

· Stowage Category A

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable

· Transport/Additional information:

· ADR/RID/ADN

· Limited quantities (LQ) 5L

· Transport category 3

· Tunnel restriction code D/E

· Remarks: ≤ 5 l: 2.2.3.1.5 ADR

· IMDG

· Limited quantities (LQ) 5L

· Remarks: ≤ 5 l: 2.3.2.5 IMDG

(Contd. on page 10)

Safety data sheet

according to UK REACH



Printing date 01.09.2026

Version number 22 (replaces version 21)

Revision: 01.09.2026

Trade name: Rittal Lackstift

(Contd. of page 9)

· **UN "Model Regulation":**UN 1263 PAINT, 3, III, ENVIRONMENTALLY
HAZARDOUS**SECTION 15: Regulatory information**· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Poisons Act**· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**· **Named dangerous substances - ANNEX I** None of the ingredients is listed.· **Seveso category P5c** FLAMMABLE LIQUIDS· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t· **National regulations:**· **Additional classification according to Decree on Hazardous Materials, Annex II:**

Class	Share in %
NK	50-100

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 11)

GB

Safety data sheet

according to UK REACH

Printing date 01.09.2026

Version number 22 (replaces version 21)

Revision: 01.09.2026

Trade name: Rittal Lackstift

(Contd. of page 10)

EUH205 Contains epoxy constituents. May produce an allergic reaction.

· **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**