Underwriters Laboratories Inc.®			Melvi	Northbrook, Illinois • (847) 272–8800 Melville, New York • (516) 271–6200		
				Santa Clara, California + (408) 985–2400 Research Triangle Park, North Carolina + (919) 549–1400		
				Cama	as, Washington + (360) 817-5	500
CER	TIFICATE	OF	COM	<b>PLI</b>	ANCE	
<u> </u>	ERTIFICATE NUMBER:	2906	598-76083			
C	ISSUEDATE:		29, 199			
Issued to:	Rittal-We Auf Dem S			GmbH & Co	D. KG	
	Postfach	1662, H	erborn,	GERMANY		
Report Reference:	March 31,	1986				
This is to Certify that						
representative samples of	DK-PS, PS Panel Enc	(1) 13 15 1500		ies Indus	strial Control	
Have been investigated by Certificate.	y Underwriters Laboratorie	s Inc. in ac	ccordance w	vith the Stand	dard(s) indicated on this	ł
	y Underwriters Laboratorie UL 508 In					ł
Certificate.	UL 508 In	dustria Max D.	l Contro	l Equipme	ent Environmental	ł
Certificate.		dustria	l Contro	l Equipme	ent	ł
Certificate.	UL 508 In Box Type	dustria Max D. Width 1800 2100	l Contro imensions Height 2200 2200	l Equipme (mm) Depth 1000 800	Environmental Type(s) 1, 12 1, 12	ł
Certificate. Standard(s) for Safety:	UL 508 In Box Type PS PS Stainless Steel DK-PS	dustria Max D. Width 1800 2100 2100	l Contro imensions Height 2200 2200 2200	1 Equipme (mm) Depth 1000 800 800	Environmental Type(s) 1, 12 1, 12 1, 12	5
Certificate. Standard(s) for Safety:	UL 508 In Box Type PS PS Stainless Steel DK-PS DK-PS w/Glazed Door	dustria Max D. Width 1800 2100 2100 800	l Contro imensions Height 2200 2200 2200 2200	l Equipme (mm) Depth 1000 800 800 800 800	Environmental Type(s) 1, 12 1, 12 1, 12 1, 12 1, 12	5
Certificate. Standard(s) for Safety:	UL 508 In Box Type PS PS Stainless Steel DK-PS DK-PS w/Glazed Door DK-PS w/Cable Entry	dustria Max D. Width 1800 2100 800 2100	l Contro imensions Height 2200 2200 2200 2200 2200	1 Equipme (mm) Depth 1000 800 800	Environmental Type(s) 1, 12 1, 12 1, 12	1
Certificate. Standard(s) for Safety:	UL 508 In Box Type PS PS Stainless Steel DK-PS DK-PS w/Glazed Door	dustria Max D. Width 1800 2100 2100 800	l Contro imensions Height 2200 2200 2200 2200	1 Equipme (mm) Depth 1000 800 800 800 800 800 800	Environmental Type(s) 1, 12 1, 12 1, 12 1, 12 1, 12 1, 12 1	3
Certificate. Standard(s) for Safety:	UL 508 In Box Type PS PS Stainless Steel DK-PS DK-PS w/Glazed Door DK-PS w/Cable Entry MC PS-EMC PS-IVS	dustria Max D. Width 1800 2100 2100 800 2100 1000 1000 2100	l Contro imensions Height 2200 2200 2200 2200 2200 2200 2200 2200 2200	1 Equipme (mm) Depth 1000 800 800 800 800 800 800 800 800 80	Environmental Type(s) 1, 12 1, 12 1, 12 1, 12 1, 12 1 1, 12 1 1, 12 1	3
Certificate. Standard(s) for Safety:	UL 508 In Box Type PS PS Stainless Steel DK-PS W/Glazed Door DK-PS W/Glazed Door DK-PS W/Cable Entry MC PS-EMC PS-IVS PC-Based on PS	dustria Max D. Width 1800 2100 2100 2100 2100 1000 1000 2100 1200	l Contro imensions Height 2200 2200 2200 2200 2200 2200 2200 22	1 Equipme (mm) Depth 800 800 800 800 800 800 800 800 800 80	Environmental Type(s) 1, 12 1, 12 1, 12 1, 12 1, 12 1, 12 1 1, 12 1 1, 12 1 1, 12 1, 12	3
Certificate. Standard(s) for Safety:	UL 508 In Box Type PS PS Stainless Steel DK-PS w/Glazed Door DK-PS w/Cable Entry MC PS-EMC PS-EMC PS-TVS PC-Based on PS PC Stainless Steel	dustria Max D. Width 2100 2100 800 2100 1000 1000 1200 2100 1200 2100	l Contro imensions Height 2200 2200 2200 2200 2200 2200 2200 22	1 Equipme (mm) Depth 1000 800 800 800 800 800 800 800 800 80	Environmental Type(a) 1, 12 1, 12 1, 12 1, 12 1, 12 1, 12 1 1, 12 1 1, 12 1, 12 1, 12 1, 12 1, 12	3
Certificate. Standard(s) for Safety: Additional Information:	UL 508 In Box Type PS PS Stainless Steel DK-PS w/Glazed Door DK-PS w/Glazed Door DK-PS w/Cable Entry MC PS-EMC PS-IVS PC-Based on PS PC Stainless Steel PC Operating Housing	dustria Max D. Width 1800 2100 2100 2100 1000 1000 2100 2100	l Contro imensions Height 2200 2200 2200 2200 2200 2200 2200 22	l Equipme (mm) Depth 1000 800 800 800 800 800 800 800 800 80	Environmental Type(s) 1, 12 1, 12 1, 12 1, 12 1, 12 1, 12 1 1, 12 1, 12 1, 12 1, 12 1, 12 1, 12 1, 12	3
Certificate. Standard(s) for Safety: Additional Information:	UL 508 In Box Type PS PS Stainless Steel DK-PS w/Glazed Door DK-PS w/Glazed Door DK-PS w/Cable Entry MC PS-EMC PS-IVS PC-Based on PS PC Stainless Steel PC Operating Housing maring the UL Listing Ma	dustria Max D. Width 1800 2100 2100 2100 1000 1000 2100 2100	l Contro imensions Height 2200 2200 2200 2200 2200 2200 2200 22	l Equipme (mm) Depth 1000 800 800 800 800 800 800 800 800 80	Environmental Type(s) 1, 12 1, 12 1, 12 1, 12 1, 12 1, 12 1 1, 12 1, 12 1, 12 1, 12 1, 12 1, 12 1, 12	1
Certificate. Standard(s) for Safety: Additional Information: Only those products be Listing and Follow-Up The UL Listing Mark generally in	UL 508 In Box Type PS PS Stainless Steel DK-PS w/Glazed Door DK-PS w/Cable Entry MC PS-EMC PS-IVS PC-Based on PS PC Stainless Steel PC Operating Housing earing the UL Listing Max Service.	dustria Max D. Width 1900 2100 2100 2000 1000 1000 1200 2100 600 rk should	l Contro imensions Height 2200 2200 2200 2200 2200 2200 2200 22	(mm) Depth 1000 800 800 800 800 800 800 80	Environmental Type (s) 1, 12 1, 12	or
Certificate. Standard(s) for Safety: Additional Information: Only those products be Listing and Follow-Up The UL Listing Mark generally in abbreviations such as "Und Lab	UL 508 In Box Type PS PS Stainless Steel DK-PS DK-PS w/Glazed Door DK-PS w/Glazed Door DK-PS w/Cable Entry MC PS-EMC PS-EMC PS-IVS PC-Based on PS PC Stainless Steel PC Operating Housing caring the UL Listing Mar Service.	dustria Max D. Width 1800 2100 2100 2000 1000 1000 1200 2100 600 rk should	I Contro imensions Height 2200 2200 2200 2200 2200 2200 2200 22	(mm) Depth 1000 800 800 800 800 800 800 800 800 80	Environmental Type (s) 1, 12 1, 12	or
Certificate. Standard(s) for Safety: Additional Information: Only those products be Listing and Follow-Up The UL Listing Mark generally in abbreviations such as "Und Lab	UL 508 In Box Type PS PS stainless Steel DK-PS w/Glazed Door DK-PS w/Cable Entry MC PS-EMC PS-TVS PC-Based on PS PC Stainless Steel PC Operating Housing earing the UL Listing Mar Service.	dustria Max D. Width 1800 2100 800 2100 1000 1000 2100 2100	l Contro imensions Height 2200 2200 2200 2200 2200 2200 2200 22	1 Equipme (mm) Depth 1000 800 800 800 800 800 800 800 800 80	Environmental Type (s) 1, 12 1, 12	or
Certificate. Standard(s) for Safety: Additional Information: Only those products be Listing and Follow-Up The UL Listing Mark generally in abbreviations such as "Und Lab	UL 508 In Box Type PS PS Stainless Steel DK-PS DK-PS w/Glazed Door DK-PS w/Cable Entry MC PS-EMC PS-IVS PC-Based on PS PC Stainless Steel PC Operating Housing earing the UL Listing Mar Service.	dustria Max D. Width 1800 2100 800 2100 1000 1000 2100 2100	l Contro imensions Height 2200 2200 2200 2200 2200 2200 2200 22	1 Equipme (mm) Depth 1000 800 800 800 800 800 800 800 800 600 ered as bei ratories Inc." in a control numbu Directory.	Environmental Type (s) 1, 12 1, 12	or