

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31



Printing date 09.04.2018

Revision: 09.04.2018

Trade name: Aerosol NC (Contd. of page 1) · Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing vapours/spray. P271 Use only outdoors or in a well-ventilated area. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. P312 P337+P313 If eye irritation persists: Get medical advice/attention. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · Additional information: Without adequate ventilation, explosive atmosphere/gas mix may be created. · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

| • Dangerous components: | | |
|---|--|-----------------|
| CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx | acetone 🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H330 | 25-<50% |
| CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx | butane (containing ≤ 0,1 % butadiene (203-450-8)) ♦ Flam. Gas 1, H220; ♦ Press. Gas C, H280 | 10-<25% |
| CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx | propane 🚸 Flam. Gas 1, H220; 🔗 Press. Gas C, H280 | 10-<25% |
| CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx | n-butyl acetate | 5-<10% |
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx | xylene Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 | 5-<10% |
| CAS: 9004-70-0 | nitrocellulose with water(not less than 25% water, by mass) 🔗 Expl. 1.1, H201 | 5-<10% |
| | (Cor | ntd. on page 3) |

Printing date 09.04.2018

Revision: 09.04.2018

Trade name: Aerosol NC

| | (Co | ontd. of page 2) |
|--------------------------------|---|------------------|
| CAS: 108-65-6 | 2-methoxy-1-methylethyl acetate | 2.5-<5% |
| EINECS: 203-603-9 | 🛞 Flam. Liq. 3, H226 | 1 |
| Reg.nr.: 01-2119475791-29-xxxx | | |
| CAS: 64-17-5 | ethanol | 2.5-<5% |
| EINECS: 200-578-6 | 🚸 Flam. Liq. 2, H225; 🕔 Eye Irrit. 2, H319 | |
| Reg.nr.: 01-2119457610-43-xxxx | | |
| CAS: 108-10-1 | 4-methylpentan-2-one | 2.5-<5% |
| EINECS: 203-550-1 | 🚯 Flam. Liq. 2, H225; 🚯 Acute Tox. 4, H332; Eye Irrit. 2, | |
| Reg.nr.: 01-2119473980-30-xxxx | H319; STOT SE 3, H335 | |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

(Contd. on page 4)

Printing date 09.04.2018

Revision: 09.04.2018

Trade name: Aerosol NC

(Contd. of page 3)

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Take note of emission threshold. Use only in well ventilated areas. Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

 Information about fire - and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke.
 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and receptacles:* Store in a cool location. Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Protect from heat and direct sunlight.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

| Ingredients with limit values that require monitoring at the work | place: |
|---|-----------------|
| 67-64-1 acetone | |
| WEL Short-term value: 3620 mg/m ³ , 1500 ppm | |
| Long-term value: 1210 mg/m ³ , 500 ppm | |
| 106-97-8 butane (containing ≤0,1 % butadiene (203-450-8)) | |
| WEL Short-term value: 1810 mg/m³, 750 ppm | |
| Long-term value: 1450 mg/m ³ , 600 ppm | |
| <i>Carc (if more than 0.1% of buta-1.3-diene)</i> | |
| 123-86-4 n-butyl acetate | |
| WEL Short-term value: 966 mg/m ³ , 200 ppm | |
| Long-term value: 724 mg/m³, 150 ppm | |
| 1330-20-7 xylene | |
| WEL Short-term value: 441 mg/m ³ , 100 ppm | |
| Long-term value: 220 mg/m ³ , 50 ppm | |
| Sk; BMGV | |
| 108-65-6 2-methoxy-1-methylethyl acetate | |
| WEL Short-term value: 548 mg/m ³ , 100 ppm | |
| Long-term value: 274 mg/m ³ , 50 ppm | |
| Sk | |
| 64-17-5 ethanol | |
| WEL Long-term value: 1920 mg/m³, 1000 ppm | |
| 1 | (Contd. on page |

Printing date 09.04.2018

Revision: 09.04.2018

Trade name: Aerosol NC

(Contd. of page 4)

108-10-1 4-methylpentan-2-oneWELShort-term value: 416 mg/m³, 100 ppmLong-term value: 208 mg/m³, 50 ppmSk, BMGV

· Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

108-10-1 4-methylpentan-2-one

BMGV 20 µmol/L

Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

• Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves Nitrile rubber, NBR
- \cdot Penetration time of glove material
- Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

 \cdot For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm · Eye protection:



Tightly sealed goggles

(Contd. on page 6)

Printing date 09.04.2018

Revision: 09.04.2018

Trade name: Aerosol NC

(Contd. of page 5)

| 9.1 Information on basic physical and c | chemical properties |
|---|--|
| General Information | nemicui properties |
| Appearance: | |
| Form: | Aerosol |
| Colour: | According to product specification |
| Odour: | Characteristic |
| Odour threshold: | Not determined. |
| pH-value: | Not determined. |
| Change in condition | |
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range | : Not applicable, as aerosol. |
| Flash point: | <0 °C |
| | Without propellant gas. |
| Flammability (solid, gas): | Not applicable. |
| Ignition temperature: | 365 °C |
| Decomposition temperature: | Not determined. |
| Auto-ignition temperature: | Product is not selfigniting. |
| Explosive properties: | In use, may form flammable/explosive vapour-air mixture. |
| Explosion limits: | |
| Lower: | 1.5 Vol % |
| Upper: | 13 Vol % |
| Vapour pressure at 20 °C: | 3,600 hPa |
| Density: | Not determined. |
| Relative density | Not determined. |
| Vapour density | Not determined. |
| Evaporation rate | Not applicable. |
| Solubility in / Miscibility with | |
| water: | Not miscible or difficult to mix. |
| Partition coefficient: n-octanol/water: | Not determined. |
| Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| Solvent content: | |
| Organic solvents: | 82.7 % |
| VOC (EU) | With propellant gas. Content given by weight. 82.66 % |
| Solids content: | 17.3 % |
| 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.

(Contd. on page 7)

Printing date 09.04.2018

Revision: 09.04.2018

(Contd. of page 6)

Trade name: Aerosol NC

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: Possible in traces.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- · **vPvB:** Ikke relevant.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

15 01 10* packaging containing residues of or contaminated by hazardous substances

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 8)

Printing date 09.04.2018

Revision: 09.04.2018

Trade name: Aerosol NC

(Contd. of page 7)

| 14.1 UN-Number ADR, IMDG, IATA | UN1950 |
|--|--|
| 14.2 UN proper shipping name ADR IMDG IATA | 1950 AEROSOLS AEROSOLS AEROSOLS, flammable |
| 14.3 Transport hazard class(es) ADR | |
| | |
| Class Label | 2 5F Gases. 2.1 |
| IMDG, IATA | 2.1 |
| | |
| Class Label | 2.1 2.1 |
| 14.4 Packing group ADR, IMDG, IATA | Void not classified |
| 14.5 Environmental hazards: Marine pollutant: | No |
| 14.6 Special precautions for user Danger code (Kemler): | Warning: Gases. |
| EMS North and | not classified |
| EMS Number: Stowage Code | F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre |
| | Category A. For AEROSOLS with a capacity above 1 litre Category B. For WASTE AEROSOLS: Category C, Clea |
| Segregation Code | of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capacit |
| | above 1 litre: Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2. |
| 14.7 Transport in bulk according to Ann Marpol and the IBC Code | |
| Transport/Additional information: | |
| ADR | |
| Limited quantities (LQ) | IL Code: F0 |
| Excepted quantities (EQ) | Code: E0 Not permitted as Excepted Quantity |

Printing date 09.04.2018

Revision: 09.04.2018

| Trade name: Aerosol NC | | |
|----------------------------------|------------------------------------|--------------------|
| | | (Contd. of page 8) |
| · Transport category | 2 | |
| • Tunnel restriction code | D | |
| ·IMDG | | |
| · Limited quantities (LQ) | 1L | |
| \cdot Excepted quantities (EQ) | Code: E0 | |
| | Not permitted as Excepted Quantity | |
| · UN "Model Regulation": | UN 1950 AEROSOLS, 2.1 | |


SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40

· National regulations:

· Technical instructions (air):



- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H201 Explosive; mass explosion hazard. H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. · Department issuing SDS: Product safety department · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 10)

GB

Printing date 09.04.2018

Revision: 09.04.2018

Trade name: Aerosol NC

(Contd. of page 9)

GB

vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives – Division 1.1 Flam. Gas 1: Flammable gases – Category 1 Aerosol 1: Aerosols – Category 1 Press. Gas C: Gases under pressure – Compressed gas Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3