

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Kontaktlack SO 801

Version number: 4.0
Replaces version of: 2017-06-12 (3)

Revision: 2018-08-16
First version: 2013-01-09

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	<u>Kontaktlack SO 801</u>
Registration number (REACH)	not relevant (mixture)
CAS number	not relevant (mixture)
Alternative number(s)	hvm108

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Industrial use Professional use Paint Lacquer
Uses advised against	Do not use for private purposes (household)

1.3 Details of the supplier of the safety data sheet

Heinrich van Megen KG
Industriering Ost 80
D-47906 Kempen
Germany

Telephone: +49 (0) 2152 - 2063 - 0
Telefax: +49 (0) 2152 - 2063 - 63

e-mail (competent person) sdb@csb-online.de

Please do not use this e-mail adress to ask for the latest safety data sheet. For this purpose contact Heinrich van Megen KG.

1.4 Emergency telephone number

As above or next toxicological information centre.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Classification				
Section	Hazard class	Category	Hazard class and category	Hazard statement
2.6	flammable liquid	2	Flam. Liq. 2	H225
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319

Kontaktlack SO 801

Classification				
Section	Hazard class	Category	Hazard class and category	Hazard statement
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
4.1A	hazardous to the aquatic environment - acute hazard	1	Aquatic Acute 1	H400
4.1C	hazardous to the aquatic environment - chronic hazard	2	Aquatic Chronic 2	H411

for full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word danger

Pictograms

GHS02, GHS07,
GHS09



Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER/doctor/.../if you feel unwell.

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

Hazardous ingredients for labelling n-butyl acetate
acetone

Kontaktlack SO 801

2.3 Other hazards

There is no additional information.

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Hazardous ingredients							
Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes	Specific Conc. Limits	M-Factors
n-butyl acetate	CAS No 123-86-4 EC No 204-658-1 Index No 607-025-00-1 REACH Reg. No 01- 211948549 3-29-xxxx	25 - < 5 0	Flam. Liq. 3 / H226 STOT SE 3 / H336	 	GHS- HC		
acetone	CAS No 67-64-1 EC No 200-662-2 Index No 606-001-00-8 REACH Reg. No 01- 211947133 0-49-xxxx	25 - < 5 0	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	 	GHS- HC IOELV		

Kontaktlack SO 801

Hazardous ingredients							
Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes	Specific Conc. Limits	M-Factors
Copper	CAS No 7440-50-8 EC No 231-159-6 REACH Reg. No 01- 211948015 4-42-xxxx	10 – < 2 5	Aquatic Acute 1 / H400 Aquatic Chronic 3 / H412				
xylene	CAS No 1330-20-7 EC No 215-535-7 REACH Reg. No 01- 211948821 6-32-xxxx	5 – < 10	Flam. Liq. 3 / H226 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 STOT RE 2 / H373 Asp. Tox. 1 / H304	 	C(a) GHS- HC IOELV		
hydrocarbons, C9, aromatics	CAS No 64742-95-6 EC No 918-668-5 REACH Reg. No 01- 211945585 1-35-xxxx	1 – < 5	Flam. Liq. 3 / H226 STOT SE 3 / H335 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	 	GHS- HC P(b)		
Silver	CAS No 7440-22-4 EC No 231-131-3 REACH Reg. No 01- 211955566 9-21-XXXX	1 – < 5	Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410		IOELV		M-factor (acute) = 100.0 M-factor (chronic) = 10.0

Notes

C(a): Mixture of isomers

GHS- Harmonised classification (the classification of the substance corresponds to the entry in the list according to

HC: 1272/2008/EC, Annex VI)

IOELV: Substance with a community indicative occupational exposure limit value

Kontaktlack SO 801

Notes

P(b): The classification as a carcinogen or mutagen is not required. The substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 shall apply

for full text of H-phrases: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Take off immediately all contaminated clothing.

Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

In all cases of doubt, or when symptoms persist, seek medical advice.

Following inhalation

Provide fresh air.

Mouth to mouth resuscitation should be avoided. Use alternative methods, preferably with oxygen or compressed air driven apparatus.

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions.

Following skin contact

After contact with skin, wash immediately with plenty of water and soap.

Following eye contact

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth. Do not induce vomiting.

Get medical advice/attention if you feel unwell.

Notes for the doctor

none

4.2 Most important symptoms and effects, both acute and delayed

These information are not available.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

water spray, alcohol resistant foam, fire extinguishing powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition products: Section 10.

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

Solvent vapours are heavier than air and may spread along floors.

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Danger of bursting container.

Hazardous combustion products

carbon monoxide (CO), carbon dioxide (CO₂), pyrolysis products, toxic, hydrogen halides (HX)

5.3 Advice for firefighters

Keep containers cool with water spray.

In case of fire and/or explosion do not breathe fumes.

Co-ordinate firefighting measures to the fire surroundings.

Do not allow firefighting water to enter drains or water courses.

Collect contaminated firefighting water separately.

Fight fire with normal precautions from a reasonable distance.

Special protective equipment for firefighters

chemical protection suit, self-contained breathing apparatus (SCBA)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

Ventilate affected area.

Avoidance of ignition sources.

Do not breathe mist/vapours/spray.

Do not get in eyes, on skin, or on clothing.

Wearing of suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water.

Retain contaminated washing water and dispose of it.

If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advices on how to clean up a spill

Collect spillage.

Absorbent material (e.g. sand, diatomaceous earth, acid binder, universal binder, sawdust, etc.).

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal.

Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5.

Personal protective equipment: see section 8.

Incompatible materials: see section 10.

Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation.

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Vapours may form explosive mixtures with air.

Measures to protect the environment

Avoid release to the environment.

Advice on general occupational hygiene

Do not eat, drink and smoke in work areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Do not breathe mist/vapours/spray.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly after handling.

Preventive skin protection (barrier creams/ointments) is recommended.

7.2 Conditions for safe storage, including any incompatibilities

Explosive atmospheres

Keep container tightly closed and in a well-ventilated place.

Use local and general ventilation.

Keep cool.

Protect from sunlight.

Flammability hazards

Keep away from sources of ignition - No smoking.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharge.

Ground/bond container and receiving equipment.

Protect from sunlight.

Incompatible substances or mixtures

Incompatible materials: see section 10.

Protect against external exposure, such as

direct light irradiation, sunlight

Consideration of other advice

Keep away from food, drink and animal feedingstuffs.

Keep container tightly closed.

Keep cool.

Ventilation requirements

Provision of sufficient ventilation.

Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

7.3 Specific end use(s)

No information available.

Kontaktlack SO 801

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)									
Country	Name of agent	CAS No	Notation	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Source
EU	ethylbenzene	100-41-4		IOELV	100	442	200	884	2017/2398/EU
EU	xylene	1330-20-7		IOELV	50	221	100	442	2017/2398/EU
EU	acetone	67-64-1		IOELV	500	1,210			2017/2398/EU
EU	silver	7440-22-4		IOELV		0.1			2017/2398/EU
GB	ethylbenzene	100-41-4		WEL	100	441	125	552	EH40/2005
GB	butyl acetate	123-86-4		WEL	150	724	200	966	EH40/2005
GB	xylene, mixture of isomers	1330-20-7		WEL	50	220	100	441	EH40/2005
GB	acetone	67-64-1		WEL	500	1,210	1,500	3,620	EH40/2005
GB	silver	7440-22-4		WEL		0.01			EH40/2005
GB	copper	7440-50-8	dm	WEL		1		2	EH40/2005
GB	copper	7440-50-8	fume	WEL		0.2			EH40/2005

Notation

dm as dusts and mists

fume as fume

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Biological limit values						
Country	Name of agent	Parameter	Notation	Identifier	Value	Source
GB	xylene	methylhippuric acids	crea	BMGV	650 mmol/mol	EH40/2005

Notation

crea creatinine

Kontaktlack SO 801

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
n-butyl acetate	123-86-4	DNEL	300 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
n-butyl acetate	123-86-4	DNEL	600 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
n-butyl acetate	123-86-4	DNEL	300 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
n-butyl acetate	123-86-4	DNEL	600 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
n-butyl acetate	123-86-4	DNEL	11 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
n-butyl acetate	123-86-4	DNEL	11 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
acetone	67-64-1	DNEL	1,210 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
acetone	67-64-1	DNEL	186 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Copper	7440-50-8	DNEL	20 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
Copper	7440-50-8	DNEL	273 mg/kg	human, dermal	worker (industry)	chronic - local effects
Copper	7440-50-8	DNEL	137 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Copper	7440-50-8	DNEL	273 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
Copper	7440-50-8	DNEL	20 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
xylene	1330-20-7	DNEL	289 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
xylene	1330-20-7	DNEL	289 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
xylene	1330-20-7	DNEL	180 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
xylene	1330-20-7	DNEL	77 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
xylene	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
hydrocarbons, C9, aromatics	64742-95-6	DNEL	25 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Kontaktlack SO 801

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
hydrocarbons, C9, aromatics	64742-95-6	DNEL	150 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Silver	7440-22-4	DNEL	0.1 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture				
Name of substance	CAS No	Endpoint	Threshold level	Environmental compartment
n-butyl acetate	123-86-4	PNEC	0.18 mg/l	freshwater
n-butyl acetate	123-86-4	PNEC	0.018 mg/l	marine water
n-butyl acetate	123-86-4	PNEC	35.6 mg/l	sewage treatment plant (STP)
n-butyl acetate	123-86-4	PNEC	0.981 mg/kg	freshwater sediment
n-butyl acetate	123-86-4	PNEC	0.098 mg/kg	marine sediment
n-butyl acetate	123-86-4	PNEC	0.09 mg/kg	soil
n-butyl acetate	123-86-4	PNEC	0.36 mg/cm ³	freshwater
acetone	67-64-1	PNEC	10.6 mg/l	freshwater
acetone	67-64-1	PNEC	1.06 mg/l	marine water
acetone	67-64-1	PNEC	21 mg/l	water
acetone	67-64-1	PNEC	100 mg/l	sewage treatment plant (STP)
acetone	67-64-1	PNEC	30.4 mg/kg	freshwater sediment
acetone	67-64-1	PNEC	3.04 mg/kg	marine sediment
acetone	67-64-1	PNEC	29.5 mg/kg	soil
Copper	7440-50-8	PNEC	7.8 µg/l	freshwater
Copper	7440-50-8	PNEC	5.2 µg/l	marine water
Copper	7440-50-8	PNEC	230 µg/l	sewage treatment plant (STP)
Copper	7440-50-8	PNEC	87 mg/kg	freshwater sediment
Copper	7440-50-8	PNEC	676 mg/kg	marine sediment
Copper	7440-50-8	PNEC	65 mg/kg	soil
xylene	1330-20-7	PNEC	0.327 mg/l	freshwater
xylene	1330-20-7	PNEC	0.327 mg/l	marine water

Kontaktlack SO 801

Relevant PNECs of components of the mixture				
Name of substance	CAS No	Endpoint	Threshold level	Environmental compartment
xylene	1330-20-7	PNEC	6.58 mg/l	sewage treatment plant (STP)
xylene	1330-20-7	PNEC	12.46 mg/kg	freshwater sediment
xylene	1330-20-7	PNEC	12.46 mg/kg	marine sediment
xylene	1330-20-7	PNEC	2.31 mg/kg	soil
xylene	1330-20-7	PNEC	0.327 mg/l	water
Silver	7440-22-4	PNEC	0.04 µg/l	freshwater
Silver	7440-22-4	PNEC	0.86 µg/l	marine water
Silver	7440-22-4	PNEC	0.025 mg/l	sewage treatment plant (STP)
Silver	7440-22-4	PNEC	438.1 mg/kg	freshwater sediment
Silver	7440-22-4	PNEC	438.1 mg/kg	marine sediment
Silver	7440-22-4	PNEC	1.41 mg/kg	soil

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Hand protection

Material	Material thickness	Breakthrough times of the glove material
these information are not available	these information are not available	these information are not available

Wear suitable gloves.

Chemical protection gloves are suitable, which are tested according to EN 374.

Check leak-tightness/impermeability prior to use.

In the case of wanting to use the gloves again, clean them before taking off and air them well.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Other protection measures

Protective clothing against liquid chemicals.

Kontaktlack SO 801

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Type: AX (gas filters and combined filters against low-boiling point organic compounds, colour code: Brown).

Environmental exposure controls

Use appropriate container to avoid environmental contamination.

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Form	fluid
Colour	Copper coloured
Odour	solvent-like
Odour threshold	these information are not available

Other safety parameters

pH (value)	these information are not available
Melting point/freezing point	these information are not available
Initial boiling point and boiling range	≥55 °C
Flash point	-19 °C
Evaporation rate	these information are not available
Flammability (solid, gas)	not relevant (fluid)

Explosive limits

Lower explosion limit (LEL)	these information are not available
Upper explosion limit (UEL)	these information are not available
Vapour pressure	240 hPa at 20 °C
Density	1.1 g/cm ³ at 20 °C
Vapour density	these information are not available
Relative density	1.1 at 20 °C (water = 1)

Solubility(ies)

Water solubility	not miscible in any proportion
------------------	--------------------------------

Kontaktlack SO 801

Partition coefficient

n-octanol/water (log KOW)	these information are not available
Auto-ignition temperature	370 °C
Relative self-ignition temperature for solids	not relevant (Fluid)
Decomposition temperature	these information are not available

Viscosity

Kinematic viscosity	50 ^S / _{ISO 4mm} at 20 °C
Dynamic viscosity	these information are not available
Explosive properties	not explosive
Oxidising properties	shall not be classified as oxidising

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

Risk of ignition.

If heated:

risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharge.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

10.5 Incompatible materials

oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known.

Hazardous combustion products: see section 5.

Kontaktlack SO 801

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification procedure

If not otherwise specified the classification is based on:
Ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Acute toxicity of components of the mixture						
Name of substance	CAS No	Exposure route	Endpoint	Value	Species	Method
n-butyl acetate	123-86-4	oral	LD50	12,789 mg/kg	rat, male	OECD Guideline 423
n-butyl acetate	123-86-4	oral	LD50	10,760 mg/kg	rat, female	OECD Guideline 423
n-butyl acetate	123-86-4	dermal	LD50	>14,000 mg/kg	rabbit	OECD Guideline 402
acetone	67-64-1	oral	LD50	5,800 mg/kg	rat, female	OECD Guideline 401
acetone	67-64-1	dermal	LD50	>15,800 mg/kg	rabbit	
acetone	67-64-1	inhalation: vapour	LC50	76 mg/l/4h	rat	
Copper	7440-50-8	inhalation: dust/mist	LC50	5.11 mg/l/4h	rat	OECD Guideline 436
xylene	1330-20-7	oral	LD50	5,627 mg/kg	mouse, male	EU method B.1
xylene	1330-20-7	oral	LD50	3,523 mg/kg	rat, male	EU method B.1
xylene	1330-20-7	inhalation: vapour	LC50	27,571 mg/m ³ /4h	rat, male	EU method B.2
hydrocarbons, C9, aromatics	64742-95-6	oral	LD50	3,492 mg/kg	rat, female	OECD Guideline 401
hydrocarbons, C9, aromatics	64742-95-6	dermal	LD50	>3,160 mg/kg	rabbit	OECD Guideline 402
hydrocarbons, C9, aromatics	64742-95-6	inhalation: vapour	LC50	>6,193 mg/m ³ /4h	rat	OECD Guideline 403
Silver	7440-22-4	oral	LD50	>2,000 mg/kg	rat	OECD 401
Silver	7440-22-4	dermal	LD50	>2,000 mg/kg	rat	OECD 402

Kontaktlack SO 801

Acute toxicity of components of the mixture						
Name of substance	CAS No	Exposure route	Endpoint	Value	Species	Method
Silver	7440-22-4	inhalation: dust/mist	LC50	>5.16 mg/l/4h	rat	OECD 436

Skin corrosion/irritation

Classification could not be established because:
Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

Classification could not be established because:
Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Respiratory sensitisation

Classification could not be established because:
Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Germ cell mutagenicity

Classification could not be established because:
Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Carcinogenicity

Classification could not be established because:
Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Reproductive toxicity

Classification could not be established because:
Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Classification could not be established because:
Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Other information

Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity (acute)

Very toxic to aquatic organisms.

Test data are not available for the complete mixture.

Aquatic toxicity (acute) of components of the mixture

Aquatic toxicity (acute) of components of the mixture						
Name of substance	CAS No	Endpoint	Value	Species	Method	Exposure time
n-butyl acetate	123-86-4	LC50	18 mg/l	fathead minnow (Pimephales promelas)	OECD Guideline 203	96 h
n-butyl acetate	123-86-4	EC50	18 mg/l	fathead minnow (Pimephales promelas)	OECD Guideline 203	96 h
n-butyl acetate	123-86-4	EC50	44 mg/l	daphnia magna		48 h
n-butyl acetate	123-86-4	ErC50	397 mg/l	algae (pseudokirchneriella subcapitata)	OECD Guideline 201	72 h
acetone	67-64-1	LC50	5,540 mg/l	rainbow trout (Oncorhynchus mykiss)		96 h
acetone	67-64-1	LC50	8,120 mg/l	fathead minnow (Pimephales promelas)	OECD Guideline 203	96 h
acetone	67-64-1	LC50	8,800 mg/l	daphnia pulex		48 h
Copper	7440-50-8	LC50	193 µg/l	fathead minnow (pimephales promelas)		96 h
xylene	1330-20-7	IC50	1 mg/l	daphnia magna	OECD Guideline 202	24 h
xylene	1330-20-7	ErC50	4.7 mg/l	algae		72 h
hydrocarbons, C9, aromatics	64742-95-6	EL50	3.2 mg/l	daphnia magna	OECD Guideline 202	48 h
hydrocarbons, C9, aromatics	64742-95-6	LL50	9.2 mg/l	rainbow trout (Oncorhynchus mykiss)	OECD Guideline 203	96 h
hydrocarbons, C9, aromatics	64742-95-6	ErC50	0.42 mg/l	algae (pseudokirchneriella subcapitata)	OECD Guideline 201	72 h

Kontaktlack SO 801

Aquatic toxicity (acute) of components of the mixture						
Name of substance	CAS No	Endpoint	Value	Species	Method	Exposure time
hydrocarbons, C9, aromatics	64742-95-6	EbC50	0.29 mg/l	algae (pseudokirchneriella subcapitata)	OECD Guideline 201	48 h
Silver	7440-22-4	LC50	1.2 µg/l	fathead minnow (Pimephales promelas)		96 h
Silver	7440-22-4	LC50	0.22 µg/l	daphnia magna		48 h

Aquatic toxicity (chronic)

Toxic to aquatic life with long lasting effects.

Test data are not available for the complete mixture.

Aquatic toxicity (chronic) of components of the mixture

Aquatic toxicity (chronic) of components of the mixture						
Name of substance	CAS No	Endpoint	Value	Species	Method	Exposure time
n-butyl acetate	123-86-4	EC50	34.2 mg/l	daphnia magna	OECD Guideline 211	21 d
n-butyl acetate	123-86-4	LC50	43.5 mg/l	daphnia magna	OECD Guideline 211	21 d
n-butyl acetate	123-86-4	NOEC	23.2 mg/l	daphnia magna	OECD Guideline 211	21 d
n-butyl acetate	123-86-4	LOEC	47.6 mg/l	daphnia magna	OECD Guideline 211	21 d
acetone	67-64-1	NOEC	>1,106 - <2,212 mg/l	daphnia magna		28 d
acetone	67-64-1	LOEC	2,212 mg/l	daphnia magna		28 d
Copper	7440-50-8	NOEC	11.4 µg/l	rainbow trout (Oncorhynchus mykiss)		45 d
xylene	1330-20-7	EL50	2.9 mg/l	aquatic invertebrates		21 d
xylene	1330-20-7	ErC50	4.36 mg/l	algae		73 h
xylene	1330-20-7	EC50	2.2 mg/l	algae		73 h
xylene	1330-20-7	NOEC	>1.3 mg/l	rainbow trout (Oncorhynchus mykiss)		56 d
xylene	1330-20-7	LOEC	3.16 mg/l	aquatic invertebrates		21 d

Kontaktlack SO 801

Aquatic toxicity (chronic) of components of the mixture						
Name of substance	CAS No	Endpoint	Value	Species	Method	Exposure time
xylene	1330-20-7	growth (EbCx) 10%	1.91 mg/l	aquatic invertebrates		21 d

12.2 Persistence and degradability

Degradability of components of the mixture

Degradability of components of the mixture					
Name of substance	CAS No	Process	Degradation rate	Time	Method
n-butyl acetate	123-86-4	oxygen depletion	83 %	28 d	OECD Guideline 301 D
acetone	67-64-1	carbon dioxide generation	90.9 %	28 d	OECD Guideline 301 B
hydrocarbons, C9, aromatics	64742-95-6	carbon dioxide generation	78 %	28 d	OECD Guideline 301

Biodegradation

Data are not available.

Persistence

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Bioaccumulative potential of components of the mixture			
Name of substance	CAS No	BCF	Log KOW
n-butyl acetate	123-86-4		2.3 (pH value: 7, 25 °C)
acetone	67-64-1		-0.24
xylene	1330-20-7	25.9	3.12
hydrocarbons, C9, aromatics	64742-95-6		~4

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Kontaktlack SO 801

12.6 Other adverse effects

Data are not available.

Endocrine disrupting potential

None of the ingredients are listed.

Remarks

Wassergefährdungsklasse, WGK (water hazard class): 3

SECTION 13: Disposal considerations

13.1 Waste treatment methods

This material and its container must be disposed of as hazardous waste.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1	UN number	1263
14.2	UN proper shipping name	PAINT
14.3	Transport hazard class(es)	
	Class	3
14.4	Packing group	II
14.5	Environmental hazards	hazardous to the aquatic environment
	Environmentally hazardous substance (aquatic environment)	Copper
14.6	Special precautions for user	
		Provisions for dangerous goods (ADR) should be complied within the premises.
14.7	Transport in bulk according to Annex II of MARPOL and the IBC Code	
		The cargo is not intended to be carried in bulk.
14.8	<u>Information for each of the UN Model Regulations</u>	
	Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)	
	UN number	1263

Kontaktlack SO 801

Proper shipping name	UN1263, PAINT, 3, II, (D/E), environmentally hazardous, special provision 640D
Class	3
Classification code	F1
Packing group	II
Danger label(s)	3, fish and tree
 	
Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	163, 367, 640D, 650
Excepted quantities (EQ)	E2
Limited quantities (LQ)	5 L
Transport category (TC)	2.
Tunnel restriction code (TRC)	D/E
Hazard identification No	33
Emergency Action Code	3YE

International Maritime Dangerous Goods Code (IMDG)

UN number	1263
Proper shipping name	UN1263, PAINT, 3, II, -19°C c.c., MARINE POLLUTANT
Class	3
Marine pollutant	yes (hazardous to the aquatic environment)
Packing group	II
Danger label(s)	3, fish and tree
 	
Special provisions (SP)	163, 367
Excepted quantities (EQ)	E2
Limited quantities (LQ)	5 L
EmS	F-E, <u>S-E</u>
Stowage category	B

International Civil Aviation Organization (ICAO-IATA/DGR)

Kontaktlack SO 801

UN number	1263
Proper shipping name	UN1263, Paint, 3, II
Class	3
Environmental hazards	yes (hazardous to the aquatic environment)
Packing group	II
Danger label(s)	3
	
Special provisions (SP)	A3, A72, A192
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)			
Name of substance	Name acc. to inventory	CAS No	Restriction
Kontaktlack SO 801	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3
xylene	toluene	108-88-3	R48
xylene	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3
xylene	flammable / pyrophoric		R40
Copper	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3
Silver	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3
n-butyl acetate	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3
n-butyl acetate	flammable / pyrophoric		R40

Kontaktlack SO 801

Dangerous substances with restrictions (REACH, Annex XVII)			
Name of substance	Name acc. to inventory	CAS No	Restriction
hydrocarbons, C9, aromatics	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3
hydrocarbons, C9, aromatics	flammable / pyrophoric		R40
acetone	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3
acetone	flammable / pyrophoric		R40

Legend

- R3
1. Shall not be used in:
 - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
 - tricks and jokes,
 - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
 2. Articles not complying with paragraph 1 shall not be placed on the market.
 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
 - can be used as fuel in decorative oil lamps for supply to the general public, and,
 - present an aspiration hazard and are labelled with R65 or H304,
 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
 - (a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: 'Keep lamps filled with this liquid out of the reach of children'; and, by 1 December 2010, 'Just a sip of lamp oil - or even sucking the wick of lamps - may lead to life-threatening lung damage';
 - (b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter may lead to life threatening lung damage';
 - (c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
 6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.
 7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.

Kontaktlack SO 801

Legend

- R40
1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:
 - metallic glitter intended mainly for decoration,
 - artificial snow and frost,
 - 'whoopee' cushions,
 - silly string aerosols,
 - imitation excrement,
 - horns for parties,
 - decorative flakes and foams,
 - artificial cobwebs,
 - stink bombs.
 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: 'For professional users only'.
 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).
 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
- R48
- Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

none of the ingredients are listed

Seveso Directive

2012/18/EU (Seveso III)				
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements		Notes
E1	environmental hazards (hazardous to the aquatic environment, cat. 1)	100	200	56)
P5c	flammable liquids (cat. 2, 3)	5,000	50,000	51)

Notation

- 51) flammable liquids, categories 2 or 3 not covered by P5a and P5b
56) hazardous to the Aquatic Environment in category Acute 1 or Chronic 1

VOC Deco-Paint Directive 2004/42/EC

VOC content	65 %. 715 g/l.
-------------	-------------------

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II

none of the ingredients are listed

Kontaktlack SO 801

Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

Pollutant release and transfer registers (PRTR)			
Name of substance	CAS No	Remarks	Threshold for releases to air (kg/year)
xylene	1330-20-7	(17) (11)	
Copper	7440-50-8	(8)	100

Legend

- (11) Single pollutants are to be reported if the threshold for BTEX (the sum parameter of benzene, toluene, ethyl benzene, xylenes) is exceeded
- (17) Total mass of xylene (ortho-xylene, meta-xylene, para-xylene)
- (8) All metals shall be reported as the total mass of the element in all chemical forms present in the release

Directive 2000/60/EC establishing a framework for Community action in the field of water policy (WFD)

none of the ingredients are listed

Regulation 98/2013/EU on the marketing and use of explosives precursors

Explosives precursors which are subject to restrictions				
Name of substance	CAS No	Type of registration	Remarks	Limit value
acetone	67-64-1	Annex II		

Legend

annex II Substances on their own or in mixtures or in substances for which suspicious transactions shall be reported

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.
Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Indication of changes: Section 2, 3, 8, 11, 12, 14, 15

Abbreviations and acronyms

Abbreviations and acronyms	
Abbr.	Descriptions of used abbreviations
2017/2398/EU	Directive of the European Parliament and of the Council amending Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work

Kontaktlack SO 801

Abbreviations and acronyms	
Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
BCF	Bioconcentration factor
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
log KOW	n-Octanol/water

Kontaktlack SO 801

Abbreviations and acronyms	
Abbr.	Descriptions of used abbreviations
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
M-factor	Means a multiplying factor. It is applied to the concentration of a substance classified as hazardous to the aquatic environment acute category 1 or chronic category 1, and is used to derive by the summation method the classification of a mixture in which the substance is present
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
SVHC	Substance of Very High Concern
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN).

International Maritime Dangerous Goods Code (IMDG).

Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties.

Health hazards.

Environmental hazards.

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Kontaktlack SO 801

List of relevant phrases (code and full text as stated in chapter 2 and 3)

List of relevant phrases (code and full text as stated in chapter 2 and 3)	
Code	Text
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Responsible for the safety data sheet

C.S.B. GmbH
Düsseldorfer Str. 113
47809 Krefeld, Germany

Telephone: +49 (0) 2151 - 652086 - 0
Telefax: +49 (0) 2151 - 652086 - 9
e-Mail: info@csb-online.de
Website: www.csb-online.de

Disclaimer

This information is based upon the present state of our knowledge.
This SDS has been compiled and is solely intended for this product.