


Rittal – The System.

Faster – better – everywhere.

Optimum surface protection

Our expertise – your benefit.



ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP

The three-phase coating procedure

The three-phase surface finish provides optimum corrosion protection and is resistant to mineral oils, lubricants, machining emulsions and solvents such as those used in cleaning. Rittal offers a paint finish as standard that is also used in the automotive industry. And this quality is also guaranteed by way of continuous process monitoring.

The result: a durable, long-lasting, and visually appealing powder coating—ideal for the most demanding industrial applications.

Textured powder coating

Erichsen cupping test to DIN EN ISO 1520	≥ 3.5 mm
Buchholz hardness to DIN EN ISO 2815	≥ 85
Cross cutting to DIN EN ISO 2409	GT 0-1
Salt spray test to DIN EN ISO 9227 NSS	Test period: 168 hours
Condensate test to DIN EN ISO 6270-2 CH	Test period: 480 hours

Finishing paint:

Powder coating min. 50 – 80 μm , polyester-epoxy resin-based (textured paint)

Primer:



Dipcoat priming, min. 10 - 20 μm , polyester or acrylic resin-based

Nanoceramic conversion layer (20 – 50 nm)

Sheet steel

EXTERIOR PAINTWORK

INTERIOR PAINTWORK



1st phase: Degreasing and nanoceramic coating

Pretreatment

- Degreasing of the raw material
- Nanoceramic conversion layer
- Eco-friendly



2nd phase: Primer

Electrophoretic dipcoat priming

- water-based polyester or acrylic resins
free of heavy metals, chromates, and
silicones
- creates even layer structures on the
surfaces, edges and hollow spaces,
thereby ensuring a complete seal
- Layer thickness approx. 10 – 20 µm
- Curing by stove-enamelling



3rd phase: Textured powder coating

Textured powder coating

- eco-friendly, heavy metal-, chromate-
and silicone-free powder-coating on
an epoxy-polyester resin basis with
excellent mechanical resistance
- decontaminatable
- Layer thickness approx. 50 – 80 µm
- Stove enamelling



Rittal – The System.

Faster – better – everywhere.

- Enclosures
- Power Distribution
- Climate Control
- IT Infrastructure
- Software & Services

You can find the contact details of all
Rittal companies throughout the world here.



www.rittal.com/contact

X1WW00036EN2607

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP