

Rittal – The System.

Faster – better – everywhere.

Aisle containment – SK 3311.163

Date : Sep 28, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Aisle containment – SK 3311.163

created: 28.09.2020 build on www.rittal.com/in-en



Product description

Design:	Door element
Description:	Slimline door element with viewing window and sliding door. Stable roof elements in a composite material with a high level of light permeability. Where required, safety glass may also be used. The aisle width is 1,200 mm.
Benefits:	Increased energy efficiency and performance capability of climate control Easily installed and retrofitted, as it is fully compatible with the VX IT rack system An inexpensive way to boost the performance of your existing installation, lengthening the investment cycle until a replacement needs to be purchased
Applications:	Depending on the application, aisle containment may be used with CRAC systems or LCP Inline as hot or cold aisle containment
Function principle:	Aisle containment is a combination of door and roof components which facilitate consistent separation of the hot and cold air in the data centre. Such separation is pivotal to saving energy and increasing the efficiency of the available climate control technology.
Material:	Sheet steel, spray-finished
Colour:	RAL 7035

Product features

Dimensions:	Width: 3600 mm Height: 2000 mm
To fit:	with depth: 1200 mm

eCl@ss 8.0/8.1:	27182102
Packs of:	1 pc(s).
Weight/pack:	150 kg
EAN:	4028177716933
Customs tariff number:	94039010
ETIM 7.0:	EC002525
ETIM 6.0:	EC002525
eCl@ss 8.0/8.1:	27182102
eCl@ss 6.0/6.1:	27182102
Product description:	SK Aisle containment, Door element, WxH: 3600x2000 mm, For enclosure depth: 1200 mm, RAL 7035
Approvals	
Certificates:	EAC