Rittal - The System.

Faster – better – everywhere.





SR 2332.235 Swing frame, large, with trim panel

State: 7/07/2025 (Source: rittal.com/au-en)



SR 2332.235 - Swing frame, large, with trim panel for TS, VX SE 800 mm wide enclosures

For 800 mm wide enclosures, 22 - 45 U, with trim panel, for mounting 482.6 mm (19") equipment.





Features

| SR 2332.235 482.6 mm (19") level, side For mounting 482.6 mm (19") equipment. Sheet steel Frame: Zinc-plated Trim panel: Spray-finished |
|---|
| For mounting 482.6 mm (19") equipment. Sheet steel Frame: Zinc-plated |
| Sheet steel Frame: Zinc-plated |
| Frame: Zinc-plated |
| • |
| |
| RAL 7035 |
| Locking rod system with double-bit lock insert Material for attaching |
| In the TS/SE with 130° or 180° opening angle, depending on the chosen mounting kit |
| Depending on the mounting situation, TS punched sections with mounting flanges 23 x 73 mm or 17 x 73 mm are required |
| |

© Rittal 2025

Features

| Note | For further installation options, see "Technical details" For two-door enclosures TS, SE with a height of 1800 or 2200 mm the next-smallest swing frame must be installed, due to collision with the lock |
|-----------------------|---|
| To fit | Enclosure type: TS VX SE Width: = 800 mm Height: ≥ 1,600 mm |
| Units | 31 U |
| To fit enclosure type | TS VX SE |
| Packs of | 1 pc(s). |
| Net weight | 16.57 |
| Gross weight | 17 |
| Customs tariff number | 94039910 |
| EAN | 4028177165137 |
| ETIM 9 | EC002620 |
| ETIM 8 | EC002620 |
| ECLASS 8.0 | 27189261 |

© Rittal 2025 3

Tender text

Large swing frame for network enclosure
31 U can be used for accommodating 482.6 mm (19") equipment.
Torsionally stiff frame, welded from rectangular tube and triple folded support section. Load capacity up to 1500 N when standard hinges are used. Distance from inside edge of door to front edge of swing frame 100 mm, may be installed deeper on a pitch pattern of 25 mm. The swing frame must be fitted to the left / to the right depending on the installation depth of the equipment. Installation position of equipment mounted to the side.

Material: sheet steel Surface finish: RAL 7035

for enclosure width: W: 800 mm

© Rittal 2025 4