

**Rittal – The System.**

Faster – better – everywhere.



**SZ 2482.310**

**Mounting frame, interface flap,  
modular**

State: 8/04/2026 (Source: [rittal.com/au-en](http://rittal.com/au-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SZ 2482.310 - Mounting frame, interface flap, modular

Suitable for universal use, for rapid access to interfaces and sockets, the affected enclosure remains closed.

## Features

|                      |  |
|----------------------|--|
| Model No.            | SZ 2482.310  |
| Design               | Mounting frame, double, with plastic flap (semi-transparent)   |
| Product description  | For universal use in all situations where rapid access to interfaces and sockets is needed. The affected enclosure remains closed and is therefore protected from ambient influences and unauthorised access.  |
| Function principle   | The mounting frame has a flap which snaps into position in various stages at opening angles of 90 to 180°. A snap fastener ensures reliable sealing. This may be locked if required.   |
| Material             | Lock: Polycarbonate<br>Mounting frame, refined die-cast zinc<br>Plastic flap: Polycarbonate (semi-transparent)   |
| Surface finish       | Mounting frame: Matt nickel-plated   |
| Colour               | Lock: RAL 7024<br>Screw terminals: yellow (RAL 1016)   |
| Mounting cut-out     | Cut-out width: 117 mm<br>Cut-out height: 91 mm   |
| Installation options | In small and compact enclosures as a programming interface for controllers<br>In IT and industrial distributors as maintenance access for networks<br>In PC enclosures and console systems for the temporary connection of additional equipment<br>in mobile Industrial Workstations for rapid connection to existing network structures<br>In command panel systems for programming and maintenance of integral components. |

## Features

---

|                                     |   |
|-------------------------------------|---|
| Dimensions                          | Width: 130 mm<br>Height: 120 mm   |
| IP protection category to IEC 60529 | IP 65 with sealed flap and proper assembly  |
| Packs of                            | 1 pc(s).  |
| Net weight                          | 0.39 kg   |
| Gross weight                        | 0.397 kg  |
| Customs tariff number               | 85369095  |
| ETIM 9                              | EC002625  |
| ETIM 8                              | EC002625  |
| ECLASS 8.0                          | 27189234  |
| Product description                 | SZ Interface flap, modular, mounting frame, double, with plastic flap, semi-transparent |

## Approvals

---

|              |                           |
|--------------|---------------------------|
| Explanations | Declaration of conformity |
|--------------|---------------------------|