

# Rittal – The System.

Faster – better – everywhere.



## SK 3301.965 Cooling medium (ready-mixed)

State: 6/04/2026 (Source: [rittal.com/au-en](http://rittal.com/au-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SK 3301.965 - Cooling medium (ready-mixed) For chillers and air-water heat exchangers

As well as protecting against frost, this cooling medium also serves to inhibit bacterial growth and provide optimum corrosion protection.

## Features

Model No.	SK 3301.965
Product description	As well as protecting against frost, this cooling medium also serves to inhibit bacterial growth and provide optimum corrosion protection.
Contents	25 l
Antifreeze/water mixture	1 : 4
Delivery form	Canister
Rifrost	Standard
Operating temperature range	-10 °C...60 °C
Packs of	1 pc(s).
Net weight	25.3 kg
Gross weight	27 kg
Customs tariff number	38200000
ETIM 9	EC001243
ETIM 8	EC001243
ECLASS 8.0	23061202
Product description	SK Cooling medium for chillers, glycol/water mixture : 1:4, container: 25 l, standard

# Tender text

RiFrost: Standard 25 l for water circuits

Apart from the recooling systems for oil and emulsion, all other recooling systems are only suitable for the cooling of water or a water/glycol mixture.

As well as protecting against frost, these also serve to impair bacterial growth and achieve optimum corrosion protection.

## Technical data

RiFrost: Standard

Glycol/water mixture: 1:4

Container: 25 l

(Safety data sheets under Downloads)