

# Rittal – The System.

Faster – better – everywhere.



## SV 3526.000

## PLS special busbars E-Cu

State: 21/05/2026 (Source: [rittal.com/au-en](http://rittal.com/au-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SV 3526.000 - PLS special busbars E-Cu

Lengths range from 495 mm to 2400 mm.



## Features

|                      |  |
|----------------------|--|
| Model No.            | SV 3526.000                                |
| Material             | E-Cu                                       |
| Bar thickness        | 5 mm                                       |
| Rated current (max.) | 684 A                                      |
| Cross-section        | 300 mm <sup>2</sup>                        |
| Note                 | May be cut individually to required length |
| Busbar type          | Busbar E-Cu                                |
| To fit busbar system | PLS 800                                    |
| To fit Model No.     | 9341.000<br>9341.050                       |
| Dimensions           | Length: 1,095 mm                           |
| To fit               | Width: = 1,200 mm                          |
| Packs of             | 3 pc(s).                                   |
| Net weight           | 8.52 kg                                    |

# Features

---

|                              |   |
|------------------------------|---|
| Gross weight                 | 8.52 kg   |
| Copper weight (kg per piece) | 2.84  |
| Customs tariff number        | 74071000  |
| ETIM 9                       | EC001522  |
| ETIM 8                       | EC001522  |
| ECLASS 8.0                   | 27370303  |
| Product description          | SV PLS special busbar E-Cu, L: 1095 mm, PLS 800, bar thickness: 5 mm, 300 mm <sup>2</sup> bar cross-section |

# Approvals

---

|              |   |
|--------------|---|
| Approvals    | UL + C-UL (listed)  |
| Explanations | Declaration of conformity<br>Declaration of conformity UK |

# Tender text

PLS special busbar E-Cu 800 A  
Bar thickness: 5 mm  
Rated current: 800 A  
Cross-section: 300 mm<sup>2</sup>  
Length: 1095 mm  
Enclosure width: 1200 mm  
(Rittal PS/TS/ES enclosure systems)