

Rittal – The System.

Faster – better – everywhere.



AS 4051.231 Wire rail WT

State: 7/04/2026 (Source: rittal.com/au-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AS 4051.231 - Wire rail WT

The pre-assembled wires are fed into the WT 26 wire rail with a cross-section of 0.5 mm² by the removal handling system.



Features

Model No.	AS 4051.231
Benefits	<ul style="list-style-type: none">Project-specific order picking for downstream processesProject-specific sorting of the wiresOptimum removal handlingBusbar system prepared for optimum workstation order-pickingNo wire sorting requiredSimplifies the wiring process with step-by-step instructions in Eplan Smart WiringIdeal in conjunction with the Wire Cart for perfect workstation order picking
Supply includes	Wire rail WT 26
Note	This gap size indicates the maximum diameter of the wire insulation.
To fit Model No.	<ul style="list-style-type: none">4051.2054051.2104051.0244051.036
Applications	For single wires with cross-section 0.5 mm ² (gap size 2.6 mm)
Packs of	1 pc(s).
Net weight	0.85 kg
Gross weight	1 kg
Customs tariff number	76169990

Features

Product description

Wire rail, 0.5 mm² for the 15-way rail system in the WT