Rittal - The System.

Faster – better – everywhere.





AS 4055.921 Perforex Milling Terminal MT 2101 S

State: 7/12/2025 (Source: rittal.com/au-en)



AS 4055.921 - Perforex Milling Terminal MT 2101 S

The Perforex Milling Terminal 2101 offers the greatest flexibility of the MT series. Supports machining of all compact and large enclosures.







Features

Model No.	AS 4055.921
Design	Enclosure machining
	Enclosure panel machining
	Patented pressure plate with integral extraction of the milling swarf
	High-performance spindle including minimal quantity lubrication
	Automatic tool testing
	DIN tools
	Pneumatic clamping device
Product description	The Perforex Milling Terminal is a 4-axis CNC machine used for
	modifying standard enclosures. It provides automated machining o enclosure panels and housings e.g. for holes, threads and cut-outs.
	The Perforex Milling Terminal 2101 offers the greatest flexibility of
	,
	the MT series. It supports machining of all compact and large enclosures.

Features

Benefits	Fast return on investment (ROI) and significantly enhanced competitiveness Short throughput times with consistently high machining quality Wire consistency with network-based software Easy to use with a clearly organised HMI and 24-inch screen Automatic tool change and integral tool length measurement Tool-friendly machining with minimal quantity lubrication system and plate Automatic swarf extraction when drilling and milling The high-performance spindle allows fast, precise, reliable machining Intuitive clamping system with pneumatic clamping device, optimised for enclosure components
Supply includes	The Perforex MT S is configured on a project-specific basis
Machinable material	Aluminium Steel Stainless steel Plastic Copper
Machine options	Signal pillar 4055.954 Side access 4055.952 Support arm system 4055.951 Enclosure machining 2000 mm 4055.953 2 additional zero points for multi-part machining 4050.066
Machine controller	Order management with the Rittal Panel Processing Center (RiPPC) Operation with Rittal HMI
Safety	Security fence to DIN EN ISO 13857 Optical protective device in front of and behind the machine Reliable braking of the axes even in the event of a power failure
Interfaces	Rittal Panel Processing Center (RiPPC) EPLAN Pro Panel Rittal Configuration System Import of DXF data
Note	We reserve the right to make technical modifications
Support area	Width: 4,600 mm Height: 2,450 mm Depth: 3,750 mm

Features

Compressed air connection	6 bar
Weight of workpiece, panel machining (max.)	250 kg
Weight of workpiece, enclosure machining (max.)	300 kg
No. of tool slots	21
Machining accuracy	± 0.2 mm
Speed X/Y-axis	60,000 mm/min
Speed Z-axis	12,000 mm/min
Spindle speed (max.)	21,000 rpm
Spindle performance (max.)	11 kW
Control voltage (DC)	24 V
Rated current max.	6.2 A
Rated operating voltage	3L+PE, 400 - 480 V, 50/60 Hz
Machining speed (max.)	1,500 mm/min
Dimensions of clampable enclosures min.	Width: 100 mm Height: 100 mm Depth: 140 mm
Dimensions of clampable enclosures max.	Width: 1,400 mm Height: 1,600 mm Depth: 1,600 mm
Dimensions of clampable enclosure panels min.	Width: 100 mm Height: 100 mm Depth: 1.25 mm
Dimensions of clampable enclosure panels max.	Width: 2,450 mm Height: 1,700 mm Depth: 5 mm
Maximum machinable area for enclosure panels	Width: 2,200 mm Height: 1,700 mm
Maximum machinable area for enclosures	Width: 1,200 mm Height: 1,600 mm

Features

Packs of	1 pc(s).
Net weight	2300
Gross weight	2720
Customs tariff number	84571090
EAN	4028177967526

Approvals

Explanations Declaration of conformity