

Rittal – The System.

Faster – better – everywhere.



DK 7010.210 Sensors

State: 23/01/2026 (Source: rittal.com/au-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



DK 7010.210 - Sensors for CMC III, PDU, LCP, IoT interface

Leak point sensor

Features

Model No.	DK 7010.210
Design	Leak point sensor
Benefits	Fast connection and automatic detection via plug & play Power is supplied via the CAN-BUS interface.
Applications	Enclosure monitoring in IT, industry and facility management Monitoring of enclosures, rooms and containers in the IT environment
Function principle	Settings can be made via the CMC III processing unit, PDU or IoT interface The leak point sensor has an external sensor fitted perpendicular to the base. The sensor monitors the base for conductive liquids (leakage) using two contacts.
Material	Plastic
Surface finish	Front: Smooth Enclosure: Textured
Colour	RAL 9005
Supply includes	Leak sensor External sensor with connection cable Mounting plate Assembly parts
Connection to the CAN bus	Direct
Interfaces	2 x RJ45 CAN bus Terminal
Dimensions	Width: 110 mm Height: 30 mm Depth: 40 mm
Operating temperature range	0 °C...45 °C

Features

Ambient humidity (non-condensing)	5...95 %
-----------------------------------	----------

Packs of	1 pc(s).
----------	----------

Net weight	0.24
------------	------

Gross weight	0.251
--------------	-------

Customs tariff number	90261029
-----------------------	----------

ETIM 9	EC002627
--------	----------

Approvals

Explanations

Declaration of conformity