Rittal - The System.

Faster - better - everywhere.





DK 7030.571 CMC III LTE unit

State: 15/11/2025 (Source: rittal.com/au-en)



DK 7030.571 - CMC III LTE unit

The CMC III LTE unit reliably informs you about alarm messages via ISDN or LTE via text message.

Features

Model No.	DK 7030.571	
Product description	For configuring a redundant transmission channel or, if there is no network infrastructure available, for alarm forwarding. The alarm signal is designed in text message format. Cover for LTE (4G), UMTS (3G) and GSM (2G) with automatic changeover function, see bands and frequencies. A standard, commercially available SIM card must be provided by the customer.	
Technical specifications	The CMC III LTE unit may be used in 4G, 3G and 2G mobile communications networks in these frequency ranges: 4G LTE band 1 (2100 MHz) 4G LTE band 3 (1800 MHz) 4G LTE band 8 (900 MHz) 4G LTE band 20 (800 MHz) 4G LTE band 28 (700 MHz) 3G UMTS band 1 (2100 MHz) 3G UMTS band 8 (900 MHz) 2G GSM (900 MHz)	
Material	Plastic	
Colour	Front: RAL 9005 Enclosure: RAL 7035	
Supply includes	CMC III LTE unit RJ12 cable Aerial with magnetic base	
Serial interface	2 x RJ12	
Dimensions	Width: 138 mm Height: 40 mm Depth: 132 mm	
Operating temperature range	0 °C55 °C	

© Rittal 2025

Features

45 °C85 °C
1 pc(s).
0.6
0.645
85176200
4028177926011
EC002627
27189253

Approvals

Explanations	Declaration of conformity	
	Declaration of conformity UK	

© Rittal 2025 3