Rittal – The System.

Faster – better – everywhere.





PK 9511.000 Polycarbonate enclosures PK

State: 7/12/2025 (Source: rittal.com/au-en)



PK 9511.000 - Polycarbonate enclosures PK without knockouts

Wall-mounted enclosure of fibreglass-reinforced polycarbonate. Protection category IP 66. Covers feature quick-release fasteners for speedy maintenance. Self-extinguishing material for safety.







Features

PK 9511.000
PK enclosure with solid cover
Use within the ambient temperature range: -35 °C+80 °C. The specified temperatures may be limited by the installed equipment.
Enclosure: Fibreglass-reinforced polycarbonate Cover grey: Fibreglass-reinforced polycarbonate, all-round foamed- in PU seal Cover screws: Polyamide Insulating bungs: Polyethylene
RAL 7035
Enclosure with cover Cover screws Insulating bungs for wall mounting screws
NEMA 4X
IP 66
IK08

© Rittal 2025

Features

Dimensions	Width: 130 mm Height: 130 mm Depth: 99 mm
Operating temperature range	-35 °C80 °C
Basic material	Polycarbonate
Packs of	4 pc(s).
Net weight	1.464
Gross weight	1.64
Customs tariff number	94037000
EAN	4028177139374
ETIM 9	EC000261
ECLASS 8.0	27180101

Approvals

Approvals	C-UL DNV-GL UL UL + C-UL (listed)
Explanations	Declaration of conformity

Tender text

Polycarbonate Housings without knockouts

Polycarbonate enclosure with solid cover without knockouts

Enclosure: Fibreglass-reinforced polycarbonate

without knockouts for cable entry

Cover: Fibreglass-reinforced polycarbonate

all-round foamed-in PU seal

© Rittal 2025 3

Cover screws: Polyamide

Insulating bungs: Polyethylene Supply includes: Cover screws

Insulating bungs for wall mounting screws

Accessories: Wall mounting bracket Protection category to IEC 60 529: IP 66 Protection category NEMA: NEMA 4X

Colour: similar to RAL 7035

Dimensions (W x H x T): 130 x 130 x 99 mm

© Rittal 2025 4