


Rittal – The System.

Faster – better – everywhere.



SZ 2500.214

LED system light

State: 22.02.2026 (Source: rittal.com/bg-bg)



SZ 2500.214 - LED system light

LED system light – the first light especially for enclosures! Highly innovative LED technology for even more light into the very last corner.



Features

| | |
|----------------------|--|
| Model No. | SZ 2500.214 |
| Design | with socket |
| Benefits | Optimum illumination of the entire enclosure Optionally with clip, screw and magnetic attachment A configuration to suit every application |
| Design | Socket 90° rotating connector Adjustable light distribution |
| Material | Light body: Extruded aluminium Light cover: Polycarbonate Light ends: PC-ABS |
| Colour | Enclosure: RAL 7016 |
| Supply includes | Assembly screws |
| Power consumption | 11 W |
| Connection options | Infeed, 3-pole Through-wiring, 3-pole Door-operated switch |
| Overvoltage category | II |

Features

| | |
|---|--|
| Protection class | II (all-insulated) |
| Light – installation type | Screw-fastening Clip attachment |
| Rated impulse withstand voltage, phase to earth | 2500 V AC |
| Rated insulation voltage | 300 V AC |
| Installation options | Directly onto the enclosure section with 25 mm pitch pattern |
| Luminous flux | 900 lm |
| Light colour | 4000 K (neutral white) |
| Note | Connection accessories should be ordered separately |
| Dimensions | Width: 437 mm Height: 80 mm Depth: 44 mm |
| Operating temperature range | -20 °C...55 °C |
| Sockets | USA/CDN (type B, NEMA 5-15) |
| Rated operating voltage | 100 V - 125 V, 1~, 50 Hz/60 Hz |
| Socket version | USA/CDN (type B, NEMA 5-15) |
| IP protection category to IEC 60529 | IP 20 |
| Packs of | 1 pc(s). |
| Net weight | 0,5 kg |
| Gross weight | 0,599 kg |
| Customs tariff number | 94054990 |
| ETIM 9 | EC000321 |
| ETIM 8 | EC000321 |
| ECLASS 8.0 | 27189241 |
| Product description | SZ System Light LED, 900 lm, L: 437 mm, 100-125 V, with socket for USA |

Approvals

| | |
|--------------|---|
| Approvals | ENEC UL |
| Explanations | Declaration of conformity Declaration of conformity UK |