

Rittal – The System.

Faster – better – everywhere.



SK 3301.920 Overflow valve

State: 10.09.2025 (Source: [rittal.com/bg-bg](https://www.rittal.com/bg-bg))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SK 3301.920 - Overflow valve

Pressostat for use in the water cycle between the recooling system and the air/water heat exchanger. It prevents an increase in pump pressure in the recooling system against the closed magnetic valve of the air/water heat exchanger outside of the cooling cycle.

Features

Model No.	SK 3301.920
Product description	Pressostat for use in the water cycle between the recooling system and the air/water heat exchanger. It prevents an increase in pump pressure in the recooling system against the closed magnetic valve of the air/water heat exchanger outside of the cooling cycle.
Material	Brass
Valve design	1" bypass valve
OUT_PRESSURE_ADJUSTMENT_RANGE	2 - 12 bar
Packs of	1 pc(s).
Net weight	1.019
Gross weight	1.046
Customs tariff number	84818073
EAN	4028177448643
ETIM 9	EC000855
ETIM 8	EC000855
ECLASS 8.0	27180704

Approvals

Certificates	EAC
--------------	-----