

Rittal – The System.

Faster – better – everywhere.



SV 3515.000

PLS busbar connectors

State: 15.05.2026 (Source: rittal.com/bg-bg)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 3515.000 - PLS busbar connectors

For connecting PLS special busbars, no drilling required.



Features

Model No.	SV 3515.000
Product description	For connecting the PLS special busbars, no drilling required.
Material	E-Cu
Surface finish	Nickel-plated
Rated current (max.)	1368 A
To fit busbars	PLS 1600
To fit Model No.	9342.000 9342.004 9342.050
Connection type	Baying connection from enclosure to enclosure
Dimensions	Length: 150 mm
Packs of	3 pc(s).
Net weight	3,81 kg
Gross weight	4,015 kg
Copper weight (kg per piece)	1,27
Customs tariff number	85369010
ETIM 9	EC000713
ETIM 8	EC000713

Features

ECLASS 8.0

27400606

Product description

SV Busbar connector, PLS 1600, bayed connection

Approvals

Approvals

ABS

DNV

Lloyds Register

UL + C-UL (listed)

Explanations

Declaration of conformity

Declaration of conformity UK

Tender text

PLS 1600 busbar connector

System

Rittal RiLine60

Description

PLS 1600 busbar connector for connecting the

PLS 1600 special busbar

Design

Baying connection from enclosure to enclosure

Material properties

E-Cu, nickel-plated

Screw M10

Tightening torque

20 Nm

Note

The use of cross members 9340240/230 is compulsory for UL 508A applications.