## Rittal – The System.

Faster – better – everywhere.





# AS 4055.480 Hole punch set, metric

State: 22.08.2025 (Source: rittal.com/bg-bg)



## AS 4055.480 - Hole punch set, metric for sheet steel

For punching round cut-outs

#### **Features**

| Model No.                   | AS 4055.480                                                                               |
|-----------------------------|-------------------------------------------------------------------------------------------|
| Design                      | With 3 cutting points                                                                     |
| Product description         | For punching round cut-outs. The hole punch is operated with a wrench or hydraulic punch. |
| Supply includes             | 5 female dies                                                                             |
|                             | 5 male dies                                                                               |
|                             | Plastic case                                                                              |
| Machinable material         | Sheet steel                                                                               |
| Maximum machinable material | 2 mm                                                                                      |
| thickness, sheet steel      | 2 mm                                                                                      |
|                             | 2 mm                                                                                      |
|                             | 2 mm                                                                                      |
|                             | 3 mm                                                                                      |
| Ø punch                     | 16,2 mm                                                                                   |
|                             | 20,4 mm                                                                                   |
|                             | 25,4 mm                                                                                   |
|                             | 32,5 mm                                                                                   |
|                             | 40,5 mm                                                                                   |
| For threads                 | M16                                                                                       |
|                             | M20                                                                                       |
|                             | M25                                                                                       |
|                             | M32                                                                                       |
|                             | M40                                                                                       |
| Note                        | When operating with wrenches, tension screws with ball bearing should be used.            |

© Rittal 2025

### **Features**

| Suitable for hydraulic bolt order | 4055.661      |
|-----------------------------------|---------------|
| number                            | 4055.661      |
|                                   | 4055.661      |
|                                   | 4055.661      |
|                                   | 4055.663      |
| Packs of                          | 1 pc(s).      |
| Net weight                        | 0.95          |
| Gross weight                      | 0.98          |
| Customs tariff number             | 82073010      |
| EAN                               | 4028177808607 |
| ETIM 9                            | EC002121      |
| ETIM 8                            | EC002121      |
| ECLASS 8.0                        | 21049047      |

© Rittal 2025 3