

# Rittal – The System.

Faster – better – everywhere.



## CP 6372.553 Comfort Panel

State: 25.06.2026 (Source: [rittal.com/bg-bg](http://rittal.com/bg-bg))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# CP 6372.553 - Comfort Panel

Aluminium enclosure, high thermal conductivity for optimum passive heat dissipation. Low weight coupled with high stability. Protection category IP 65 to IEC 60 529.



## Features

|                 |   |
|-----------------|---|
| Model No.       | CP 6372.553   |
| Design          | Support arm connection Ø 130 mm   |
| Benefits        | Aluminium enclosure, high thermal conductivity for optimum passive heat dissipation.<br>Low weight coupled with high stability<br>Compatible with all Rittal stand and support arm systems  |
| Material        | Enclosure: Extruded aluminium section<br>Corner pieces: Die-cast zinc<br>Corner protectors: Plastic   |
| General colour  | Natural anodised  |
| Colour          | Enclosure: Natural anodised<br>Corner pieces: RAL 7035<br>Corner protectors: similar to RAL 7024  |
| Supply includes | Enclosure with cut-out for support arm connection<br>3 mm double-bit lock insert may be exchanged for 41 mm lock inserts, plastic handles and T handles, type C<br>Seals and assembly parts for front panels<br>Screw-fastened rear panel, enclosure hinged at the front with side double-bit lock insert |

# Features

|                                     |   |
|-------------------------------------|---|
| Dimensions                          | Width: 628.5 mm<br>Height: 608.5 mm<br>Depth: 209 mm  |
| Installation depth                  | 191 mm  |
| IP protection category to IEC 60529 | IP 65   |
| Protection category NEMA            | NEMA 12   |
| To fit front panel width            | 520 mm  |
| To fit front panel height           | 500 mm  |
| Design                              | Servicing access from the rear  |
| Note                                | The support arm connection may be swapped over by rotating the enclosure  |
| Basic material                      | Aluminium   |
| Lock                                | Lock version: Crescent-shaped cam<br>Number of locks: 2<br>Lock insert: 3 mm double-bit   |
| Packs of                            | 1 pc(s).  |
| Net weight                          | 17 kg   |
| Gross weight                        | 18,1 kg   |
| Customs tariff number               | 94032080  |
| ETIM 9                              | EC002504  |
| ECLASS 8.0                          | 27180505  |
| Product description                 | CP Compact Panel, for front panel BH 520x500 mm, installation depth 191 mm, Extruded aluminum section, Support arm connection Ø 130 mm, Screw-fastened rear panel |

# Approvals

|           |                    |
|-----------|--------------------|
| Approvals | UL + C-UL (listed) |
|-----------|--------------------|

# Approvals

---

Explanations

Declaration of conformity

Declaration of conformity UK