

Rittal – The System.

Faster – better – everywhere.



DK 7000.630

Socket strip in a plastic housing

State: 23.05.2026 (Source: rittal.com/bg-bg)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



DK 7000.630 - Socket strip in a plastic housing

Socket strips 230 V, unrestricted use, including angular connectors, thanks to the long row arrangement of plug-type contacts.



Features

| | |
|----------------------------|--|
| Model No. | DK 7000.630 |
| Product description | 8-way socket strip for earthing-pin plug (type F, CEE 7/4) The strip may be mounted vertically on the enclosure frame or in the rear 482.6 mm (19") section. In the 482.6 mm (19") section, more than 2 U of space is required. The sockets are arranged at an angle of 45° so that angular connectors are also easily used. The connection cable is contacted in a terminal slot in the strip. The terminal slot has a separate cover and external terminals for separate earthing. |
| Material | Plastic |
| Supply includes | Connection cable Assembly screws 2 serrated washers Captive nuts M6, conductive Nuts |
| Design | Without switch |
| Sockets | 8 x D, earthing-pin (type F, CEE 7/3) |
| Length of connection cable | 2 m |
| Connection cable (type) | H05VV-F3G1.5 with wire end ferrules |
| Rated operating voltage | 230 V AC, 50 Hz |

Features

| | |
|-------------------------------|--|
| Rated voltage | 230 V AC, 50 Hz |
| Rated current (max.) | 16 A |
| Type of electrical connection | Wire end ferrules |
| Installation options | TE 7000, rear 482.6 mm (19") section (> 2 U) TE 7000, vertically mounted on the frame |
| Colour of socket | Black |
| Packs of | 1 pc(s). |
| Net weight | 0,92 kg |
| Gross weight | 1,026 kg |
| Customs tariff number | 85366990 |
| ETIM 9 | EC000330 |
| ECLASS 8.0 | 27142604 |
| Product description | DK-TS Socket strip, CEE 7/3 (type F), 8-way, 230 V, 16 A, LHD: |

Approvals

| | |
|--------------|---------------------------|
| Explanations | Declaration of conformity |
|--------------|---------------------------|

Tender text

Socket strip, 8-way, earthing pin
8-way socket strip for earthing-pin plug/version D.
The strip is made of plastic and may be mounted vertically on the TE frame or in the rear 482.6 mm (19 inch) section, more than 2 U of space is required.
The sockets are arranged at an angle of 45° so that angular connectors are also easily used.