Rittal – The System.

Faster – better – everywhere.





PK 9514.100 Polycarbonate enclosures PK

State: 30.08.2025 (Source: rittal.com/bg-bg)



PK 9514.100 - Polycarbonate enclosures PK without knockouts

Wall-mounted enclosure of fibreglass-reinforced polycarbonate. Protection category IP 66. Covers feature quick-release fasteners for speedy maintenance. Self-extinguishing material for safety.







Features

| Model No. | PK 9514.100 |
|-----------------------------------|---|
| Design | PK enclosure with transparent cover |
| Product description | Use within the ambient temperature range: -35 °C+80 °C. The specified temperatures may be limited by the installed equipment. |
| Material | Enclosure: Fibreglass-reinforced polycarbonate |
| | Cover transparent: Polycarbonate, all-round foamed-in PU seal |
| | Cover screws: Polyamide |
| | Insulating bungs: Polyethylene |
| Colour | RAL 7035 |
| Supply includes | Enclosure with cover |
| | Cover screws |
| | Insulating bungs for wall mounting screws |
| Protection category NEMA | NEMA 4X |
| Protection category to IEC 60 529 | IP 66 |
| IK Code | IK08 |
| | |

© Rittal 2025

Features

| Dimensions | Width: 180 mm Height: 110 mm Depth: 90 mm |
|-----------------------------|---|
| Operating temperature range | -35 °C80 °C |
| Basic material | Polycarbonate |
| Packs of | 2 pc(s). |
| Net weight | 0.756 |
| Gross weight | 0.856 |
| Customs tariff number | 94037000 |
| EAN | 4028177139510 |
| ETIM 9 | EC000261 |
| ECLASS 8.0 | 27180101 |

Approvals

| Approvals | C-UL |
|--------------|---------------------------|
| | DNV-GL |
| | UL |
| Explanations | Declaration of conformity |

Tender text

Polycarbonate Housings without knockouts

Polycarbonate enclosure, transparent cover without knockouts

Enclosure: Fibreglass-reinforced polycarbonate

without knockouts for cable entry

Cover: Fibreglass-reinforced polycarbonate

all-round foamed-in PU seal Cover screws: Polyamide

© Rittal 2025 3

Insulating bungs: Polyethylene Supply includes: Cover screws

Insulating bungs for wall mounting screws

Accessories: Wall mounting bracket Protection category to IEC 60 529: IP 66 Protection category NEMA: NEMA 4X

Colour: similar to RAL 7035

Dimensions (W x H x T): 180 x 110 x 90 mm

© Rittal 2025 4