

Faster – better – everywhere.





SV 9676.700 Connection plate

State: 21.08.2025 (Source: rittal.com/bg-bg)



POWER DISTRIBUTION >> CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

ENCLOSURES

SV 9676.700 - Connection plate for ring terminals

For connecting ring terminals to a Flat-PLS busbar system with 2 – 4 bars per conductor.

Features

Model No.	SV 9676.700
Product description	For connecting ring terminals to a busbar distributor system made from flat copper. Suitable for 10 mm bar thickness.
Material	Connection plate: E-Cu, nickel-plated Busbar claw: Stainless steel
Supply includes	Assembly parts (excluding screws) Grub screw
Assembly instruction	The required screw length must be selected in line with the busbar width W, i.e. length = W + fastening measurement. Screws are not included with the supply. Busbar claw with threaded insert M10
Number of bars per conductor	2
Dimensions	Thread: M12
Mounting dimensions	20 mm
Packs of	1 pc(s).
Net weight	0.6
Gross weight	0.612
Copper weight (kg per piece)	0.49
Customs tariff number	73269098
EAN	4028177625754
ETIM 9	EC002270
ECLASS 8.0	27400613

Approvals

Approvals	ABS
	DNV-GL
	Lloyds Register of Shipping
Explanations	Declaration of conformity
	Declaration of conformity UK