

Rittal – The System.

Faster – better – everywhere.



HD 1314.600

Compact enclosure HD, single-door

State: 2026-07-03 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



HD 1314.600 - Compact enclosure HD, single-door

Enclosure solution tailored to the requirements of the food and beverage industry. Roof angled forwards by 30°. Seal dyed blue to clearly distinguish it from foodstuffs



Features

| | |
|-----------------|--|
| Model No. | HD 1314.600 |
| Version | Hygienic Design Enclosures |
| Product changes | From June 2020, the compact enclosure HD, single-door, comes with the new compact enclosure AX mounting plate. |
| Material | Housing and door: Stainless steel 1.4301 (AISI 304) Mounting plate: Carbon steel HD lock inserts: Stainless steel 1.4404 (AISI 316L) Seal: Silicone, compliant with FDA Guideline 21 CFR 177.2600 |
| Surface finish | Housing and door: Brushed, grain 400, peak-to-valley height < 0.8 µm Mounting panel: Zinc-plated Seal: Blue, dyed (RAL 5010) |
| Supply includes | Housing of all-round solid construction Door with fitted seal Door hinged on the right, may be swapped to the left Mounting panel |
| Dimensions | Width: 810 mm Height, front: 430 mm Height rear: 549 mm Depth: 210 mm |

Features

| | |
|--------------------------------------|--|
| Dimensions of mounting plate (W x H) | 750 mm x 355 mm |
| Door opening angle | 125° |
| No. of locks | 2 |
| IK code | IK08 |
| Base material | Stainless steel 1.4301 (AISI 304) |
| Protection category IP to IEC 60529 | IP 66 IP X9 |
| Protection category NEMA | NEMA 1 NEMA 3 NEMA 3X NEMA 4 NEMA 4X NEMA 12 NEMA 13 |
| Type rating according to UL 50E | Type 1 Type 3 Type 3X Type 4 Type 4X Type 12 Type 13 |
| Packaging unit | 1 pc(s). |
| Net weight | 25 kg |
| Gross weight | 26 kg |
| PCF/VE (cradle-to-gate) | 84.57 |
| Customs tariff number | 94032080 |
| ETIM 9 | EC000261 |
| ETIM 8 | EC000261 |
| ECLASS 8.0 | 27180101 |
| Product description | HD Compact enclosure, WHD: 810x430(H1)x549(H2)x210 mm, Stainless steel 1.4301, with mounting plate, with hinged door and silicone seal |

Approvals

Approvals

UL + C-UL (listed)

Explanations

Declaration of conformity

Declaration of conformity UK

PCF-declaration