

Faster – better – everywhere.





KX 1550.000 E-box KX, carbon steel

POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

State: 2025-08-25 (Source: rittal.com/ca-en)



FRIEDHELM LOH GROUP

ENCLOSURES

KX 1550.000 - E-box KX, carbon steel

The small enclosure KX, E-Box KX, carbon steel offers remarkable ease of assembly and flexibility when selecting lock systems.



Features

KX 1550.000
The small enclosure KX, E-Box KX, carbon steel offers remarkable ease of assembly and flexibility when selecting lock systems.
Housing: Carbon steel
Door: Carbon steel, all-round foamed-in PU seal
Housing and door: Dipcoat primed, powder-coated on the outside
textured paint
Mounting panel: Zinc-plated
RAL 7035
Housing with door
Mounting panel
Cam lock with 3 mm double-bit insert
180° hinge
NEMA 1
NEMA 3R
NEMA 4
NEMA 12
IP 66

Features

Type rating according to UL 50E	Type 1 Type 3R Type 4 Type 12
IK code	IK08
Dimensions	Width: 200 mm Height: 400 mm Depth: 120 mm
Dimensions of mounting plate (W x H)	175 mm x 385 mm
Material thickness - enclosure	1.25 mm
Material thickness - door	1.25 mm
Material thickness – mounting plate	2 mm
Lock	No. of locks: 1
Base material	Carbon steel
Packaging unit	1 pc(s).
Net weight	4.288
Gross weight	4.62
PCF/VE (cradle-to-gate)	16.9 kg CO2 eq (Cat B)
Information regarding the PCF class	Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared
Customs tariff number	94032080
EAN	4028177816527
E-Number Sweden	E3465218
ETIM 9	EC000261
ETIM 8	EC000261
ECLASS 8.0	27180101

Approvals

Approvals	Bureau Veritas DNV-GL Lloyds Register of Shipping UL + C-UL (listed)
Certificates	Protection category
Explanations	Manufacturer's declaration Declaration of conformity Declaration of conformity UK PCF-declaration