

Rittal – The System.

Faster – better – everywhere.



KX 1555.000

E-box KX, carbon steel

State: 2026-07-02 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



KX 1555.000 - E-box KX, carbon steel

The small enclosure KX, E-Box KX, carbon steel offers remarkable ease of assembly and flexibility when selecting lock systems.



Features

| | |
|------------------------------------|--|
| Model No. | KX 1555.000 |
| Product description | The small enclosure KX, E-Box KX, carbon steel offers remarkable ease of assembly and flexibility when selecting lock systems. |
| Material | Housing: Carbon steel Door: Carbon steel, all-round foamed-in PU seal |
| Surface finish | Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting panel: Zinc-plated |
| Color | RAL 7035 |
| Supply includes | Housing with door Mounting panel Cam lock with 3 mm double-bit insert 180° hinge |
| Protection category NEMA | NEMA 1 NEMA 3R NEMA 4 NEMA 12 |
| Protection category IP to EN 60529 | IP 66 |

Features

| | |
|--------------------------------------|--|
| Type rating according to UL 50E | Type 1 Type 3R Type 4 Type 12 |
| IK code | IK08 |
| Dimensions | Width: 300 mm Height: 300 mm Depth: 120 mm |
| Dimensions of mounting plate (W x H) | 275 mm x 285 mm |
| Material thickness - enclosure | 1.25 mm |
| Material thickness - door | 1.25 mm |
| Material thickness – mounting plate | 2 mm |
| Lock | No. of locks: 1 |
| Base material | Carbon steel |
| Packaging unit | 1 pc(s). |
| Net weight | 4.8 kg |
| Gross weight | 4.954 kg |
| PCF/VE (cradle-to-gate) | 34.53 kg CO2 eq (Cat B) |
| Information regarding the PCF class | Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared |
| Customs tariff number | 84879059 |
| ETIM 9 | EC000261 |
| ETIM 8 | EC000261 |
| ECLASS 8.0 | 27180101 |
| Product description | KX E-Box, WHD: 300x300x120 mm, sheet steel, with mounting plate, with door |

Approvals

Approvals

Bureau Veritas
DNV
Lloyds Register
UL + C-UL (listed)

Certificates

Protection category

Explanations

Manufacturer's declaration
Declaration of conformity
Declaration of conformity UK
PCF-declaration