## Rittal – The System.

Faster – better – everywhere.





# KX 1588.000 E-box KX

State: 2025-11-02 (Source: rittal.com/ca-en)




#### KX 1588.000 - E-box KX Stainless steel

The E-Box KX, stainless steel offers remarkable ease of assembly and flexibility when selecting lock systems. The standard 180° hinges provide easy access to the enclosure interior.







#### **Features**

Model No.	KX 1588.000
Product description	The small enclosure KX, E-Box KX, stainless steel offers remarkable ease of assembly and flexibility when selecting lock systems. The standard 180° hinges provide easy access to the enclosure interior.
Material	Housing: Stainless steel
	Door: Stainless steel, all-round foamed-in PU seal
	Mounting plate: Carbon steel
	Stainless steel 1.4301 (AISI 304)
Surface finish	Housing and cover: Brushed, grain 180
	Mounting panel: Zinc-plated
Supply includes	Mounting panel
	Cam lock with 3 mm double-bit insert
Protection category IP to EN 60 529	IP 65
Type rating according to UL 50E	Type 1
	Type 3R
	Type 3RX
	Type 4
	Type 4X
	Type 12

© Rittal 2025 2

### Features

Dimensions	Width: 380 mm
	Height: 300 mm
	Depth: 155 mm
Dimensions of mounting plate (W	365 mm x 275 mm
x H)	
Material thickness - enclosure	1.25 mm
Material thickness - door	1.25 mm
Lock	No. of locks: 1
Base material	Stainless steel 1.4301 (AISI 304)
Packaging unit	1 pc(s).
Net weight	6.4
Gross weight	6.5
Customs tariff number	84879059
EAN	4028177919143
E-Number Sweden	E3465244
ETIM 9	EC000261
ETIM 8	EC000261
ECLASS 8.0	27180101

## Approvals

Approvals	Bureau Veritas  DNV-GL  Lloyds Register of Shipping  UL + C-UL (listed)
Explanations	Declaration of conformity

© Rittal 2025 3