Rittal – The System.

Faster – better – everywhere.





SZ 2500.211 LED system light

State: 2025-11-04 (Source: rittal.com/ca-en)



SZ 2500.211 - LED system light

LED system light - the first light designed especially for enclosures! Advanced LED technology provides even more light into the last recess.





Features

Model No.	SZ 2500.211	
Version	with socket	
Benefits	Optimum illumination of the entire enclosure	
	Option of clip-on, screw or magnetic attachment	
	A configuration to suit every application	
Version	Socket	
	90° rotating connector	
	Adjustable light distribution	
Material	Light body: Extruded aluminum	
	Light cover: polycarbonate	
	Light ends: PC-ABS	
Color	Enclosure: RAL 7016	
Supply includes	Assembly screws	
Rated power	11 W	
Connection options	Power Supply, 3-pole	
	Through-wiring, 3-pole	
	Door-operated switch	
Overvoltage category	II	

© Rittal 2025

Features

Protection category	II (total insulation)
Light – installation type	Screw fastening Clip fastening
Rated impulse withstand voltage, phase to earth	2500 V AC
Rated insulation voltage	300 V AC
Installation options	Directly onto the enclosure section with 25 mm pitch pattern
Luminous flux	900 lm
Light color	4000 K (neutral white)
Note	Connection accessories should be ordered separately
Dimensions	Width: 437 mm Height: 80 mm Depth: 44 mm
Operating temperature range	-20 °C55 °C
Outlets	GB (type G, BS 1363)
Rated operating voltage	100 V - 230 V, 1~, 50 Hz/60 Hz
Socket version	GB (type G, BS 1363)
Protection category IP to IEC 60 529	IP 20
Packaging unit	1 pc(s).
Net weight	0.5
Gross weight	0.628
Customs tariff number	94054990
EAN	4028177811355
ETIM 9	EC000321
ETIM 8	EC000321
ECLASS 8.0	27189241

© Rittal 2025 3

Approvals

Approvals	CQC-CCC ENEC
Explanations	Declaration of conformity Declaration of conformity UK

© Rittal 2025