

Rittal – The System.

Faster – better – everywhere.



SK 3124.100 Master/slave cable

State: 2026-05-12 (Source: rittal.com/ca-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SK 3124.100 - Master/slave cable for SK-BUS system

The SK BUS system allows several cooling units and air/water heat exchangers with e-Comfort controller to communicate with one another. The master/slave assembly ensures an optimal operating result for complex bayed enclosure systems.

Features

Model No.	SK 3124.100
Product description	The SK BUS system is used to enable communication between multiple cooling units and air/water heat exchangers with an e-Comfort controller. Master-slave configuration for complex bayed enclosure systems, for optimum operating results.
Technical specifications	The master-slave configuration facilitates common activation and deactivation via door limit switches, parallel activation and deactivation via a temperature setpoint, and common collective fault signals and temperature logging, thereby eliminating the need for intricate wiring.
Supply includes	3 m shielded interface cable Operating instructions for programming the cooling units
Packaging unit	1 pc(s).
Note	$nB = nK - 1$ nB: Number of order units (SK bus system) nK: Number of cooling units to be linked
Net weight	0.15 kg
Gross weight	0.221 kg
Customs tariff number	85444290
ETIM 9	EC002620
ETIM 8	EC002620
ECLASS 8.0	27189261
Product description	SK Master/slave cabel, for SK BUS system