Rittal – The System.

Faster – better – everywhere.





SK 3237.300 Blue e+ outlet filter

State: 2025-11-17 (Source: rittal.com/ca-en)




SK 3237.300 - Blue e+ outlet filter

The outlet filter is used in conjunction with the associated filter fan to dissipate lost heat out of the enclosures, to ventilate the enclosure and to protect temperature-sensitive components. This is done via the direct supply of ambient air that must be below the permissible temperature inside the enclosure.







Features

Model No.	SK 3237.300
Version	wall-mounted
Benefits	Easy filter change thanks to a new opening mechanism on the
	louvre grille
	Faster assembly on the enclosure due to optimized snap hooks
	Tool-free mounting
Material	Plastic
Color	RAL 7035
Supply includes	Outlet Filters
	Chopped fiber filter mat
Mounting cut-out	Width of opening: 92 mm
	Cut-out height: 92 mm
Suitable for Model No.	SK 3237.7xx
Dimensions	Width: 116.5 mm
	Height: 116.5 mm
	Depth: 33.2 mm

© Rittal 2025 2

Features

Protection category NEMA	Type 12 with fleece filter Type 3, 3R with fleece filter and hose-proof hood
Protection category IP to IEC 60 529	IP 54 with fleece filter IP 56 with fleece filter and hose-proof hood
Packaging unit	1 pc(s).
Net weight	0.12
Gross weight	0.155
Customs tariff number	39269097
EAN	4028177998438
ETIM 9	EC002513
ETIM 8	EC002513
ECLASS 8.0	27180706

Approvals

Approvals	UL + C-UL - FTTA
	UR + C-UR (recognized)

© Rittal 2025 3