## Rittal – The System.

Faster – better – everywhere.





# SK 3237.400 Blue e+ outlet filter

State: 2025-12-03 (Source: rittal.com/ca-en)



#### SK 3237.400 - Blue e+ outlet filter EMC

The outlet filter is used in conjunction with the associated filter fan to dissipate lost heat out of the enclosures, to ventilate the enclosure and to protect temperature-sensitive components. This is done via the direct supply of ambient air that must be below the permissible temperature inside the enclosure.







#### **Features**

| SK 3237.400   |
|---|
| wall-mounted<br>EMC   |
| Easy filter change thanks to a new opening mechanism on the louvre grille Faster assembly on the enclosure due to optimized snap hooks Tool-free mounting |
| RAL 7035  |
| Outlet Filters<br>EMC Filter Mat  |
| Width of opening: 92 mm<br>Cut-out height: 92 mm  |
| SK 3237.8xx   |
| Width: 116.5 mm<br>Height: 116.5 mm<br>Depth: 33.2 mm   |
|   |

© Rittal 2025 2

### Features

| Protection category NEMA         | Type 12 with fleece filter                        |
|----------------------------------|---|
|                                  | Type 3, 3R with fleece filter and hose-proof hood |
| Protection category IP to IEC 60 | IP 54 with fleece filter                          |
| 529                              | IP 56 with fleece filter and hose-proof hood      |
| Packaging unit                   | 1 pc(s).  |
| Net weight                       | 0.075   |
| Gross weight                     | 0.154   |
| Customs tariff number            | 39269097  |
| EAN                              | 4028177998414                                     |
| ETIM 9                           | EC002513  |
| ETIM 8                           | EC002513  |
| ECLASS 8.0                       | 27180706  |

## **Approvals**

| Approvals | UL + C-UL - FTTA       |
|-----------|------------------------|
|           | UR + C-UR (recognized) |

© Rittal 2025 3