Rittal – The System.

Faster – better – everywhere.





SK 3237.400 Blue e+ outlet filter

State: 2025-07-13 (Source: rittal.com/ca-en)



SK 3237.400 - Blue e+ outlet filter EMC

The outlet filter is used in conjunction with the associated filter fan to dissipate lost heat out of the enclosures, to ventilate the enclosure and to protect temperature-sensitive components. This is done via the direct supply of ambient air that must be below the permissible temperature inside the enclosure.







Features

SK 3237.400 wall-mounted EMC Easy filter change thanks to a new opening mechanism on the louvre grille Faster assembly on the enclosure due to optimized snap hooks Tool-free mounting
EMC Easy filter change thanks to a new opening mechanism on the louvre grille Faster assembly on the enclosure due to optimized snap hooks
louvre grille Faster assembly on the enclosure due to optimized snap hooks
RAL 7035
Outlet Filters EMC Filter Mat
Width of opening: 92 mm Cut-out height: 92 mm
SK 3237.8xx
Width: 116.5 mm Height: 116.5 mm Depth: 33.2 mm

© Rittal 2025 2

Features

Protection category NEMA	Type 12 with fleece filter
	Type 3, 3R with fleece filter and hose-proof hood
Protection category IP to IEC 60	IP 54 with fleece filter
529	IP 56 with fleece filter and hose-proof hood
Packaging unit	1 pc(s).
Net weight	0.075
Gross weight	0.154
Customs tariff number	39269097
EAN	4028177998414
ETIM 9	EC002513
ETIM 8	EC002513
ECLASS 8.0	27180706

Approvals

Approvals	UL + C-UL - FTTA
	UR + C-UR (recognized)

© Rittal 2025 3