


Faster – better – everywhere.





SK 3238.400 Blue e+ outlet filter

POWER DISTRIBUTION >> CLIMATE CONTROL

State: 2025-08-24 (Source: rittal.com/ca-en)



IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

ENCLOSURES

SK 3238.400 - Blue e+ outlet filter EMC

The outlet filter is used in conjunction with the associated filter fan to dissipate lost heat out of the enclosures, to ventilate the enclosure and to protect temperature-sensitive components. This is done via the direct supply of ambient air that must be below the permissible temperature inside the enclosure.



Features

Model No.	SK 3238.400
Version	wall-mounted
	EMC
Benefits	Easy filter change thanks to a new opening mechanism on the
	louvre grille
	Faster assembly on the enclosure due to optimized snap hooks
	Tool-free mounting
Color	RAL 7035
Supply includes	Outlet Filters
	EMC Filter Mat
Mounting cut-out	Width of opening: 124 mm
	Cut-out height: 124 mm
Suitable for Model No.	SK 3238.8xx
Dimensions	Width: 148.5 mm
	Height: 148.5 mm
	Depth: 34.2 mm

Features

Protection category NEMA	Type 12 with fleece filter Type 3, 3R, 4, 4X with fleece filter and hose-proof hood
Protection category IP to IEC 60 529	IP 54 with fleece filter IP 56 with fleece filter and hose-proof hood
Packaging unit	1 pc(s).
Net weight	0.15
Gross weight	0.217
Customs tariff number	39269097
EAN	4028177998407
ETIM 9	EC002513
ETIM 8	EC002513
ECLASS 8.0	27180706

Approvals

Approvals

UL + C-UL - FTTA UR + C-UR (recognized)