Rittal – The System.

Faster – better – everywhere.





SK 3240.710 Blue e+ filter fan

State: 2025-10-27 (Source: rittal.com/ca-en)



SK 3240.710 - Blue e+ filter fan

Complete fan unit for tool-free mounting on surfaces. Air throughput from 11 - 682.75 cfm, protection category IP 54 as standard.







Features

Model No.	SK 3240.710
Version	wall-mounted
Product description	Filter fans with diagonal fan technology are more pressure-resistant and produce more constant air performance. The diagonal outflow direction ensures a more uniform heat dissipation from the enclosure.
Benefits	Highest airflow through pleated filter in delivery condition Easy filter change thanks to a new opening mechanism on the louvre grille Faster assembly on the enclosure due to optimized snap hooks Diagonal fan technology ensures more uniform and consistent ventilation of the control cabinet through higher pressure stability. Tool-free mounting
Material	Plastic
Color	RAL 7035
Supply includes	Complete unit ready to install, including pleated filter
Fan	Diagonal, shaded pole motor
Unimpeded air flow (with chopped fiber filter)	At 50 Hz: 175 m³/h At 60 Hz: 157 m³/h

© Rittal 2025

Features

Packaging unit	1 pc(s).
Noise pressure level	At 50 Hz: 48 dB(A) At 60 Hz: 45 dB(A)
Storage temperature range	-30 °C70 °C
Operating temperature range	-30 °C55 °C
Note	For the 3237.XXX filter fan, the electrical connection is made via 2 individual wires (length approx. 300 mm) on the unit, for all other filter fans, it's made via a spring-loaded terminal
Pre-fuse	Miniature circuit-breaker/fuse: 4 A
Protection category NEMA	Type 12 with chopped fiber filter/pleated filter Type 3, 3R, 4, 4X with chopped fiber filter/pleated filter and hose- proof hood
Protection category IP to IEC 60 529	IP 54 with chopped fiber filter/pleated filter IP 55 with pleated filter and absorber mat IP 56 with chopped fiber filter/pleated filter and hose-proof hood
Mounting cut-out	Width of opening: 224 mm Cut-out height: 224 mm
Installation depth	108 mm
Dimensions	Width: 255 mm Height: 255 mm Depth: 129 mm
Rated current max.	At 50 Hz: 0.41 A At 60 Hz: 0.42 A
Rated power Pel	At 50 Hz: 35.5 W At 60 Hz: 38.2 W
Rated operating voltage	115 V, 1~, 50 Hz/60 Hz
Airflow with corresponding outlet filter including pleated filter	At 50 Hz: 191 m³/h At 60 Hz: 161 m³/h
Airflow with corresponding outlet filter including chopped fiber filter	At 50 Hz: 130 m³/h At 60 Hz: 112 m³/h
Unimpeded air flow (with pleated filter)	At 50 Hz: 218 m³/h At 60 Hz: 191 m³/h

© Rittal 2025

3

Features

Net weight	2.361
Gross weight	2.381
Customs tariff number	84145915
EAN	4028177998124
ETIM 9	EC000320
ETIM 8	EC000320
ECLASS 8.0	27180716

Approvals

Approvals	CSA
	30 - KC Korea
	UL + C-UL - FTTA
	UR + C-UR (recognized)
Explanations	Declaration of conformity

© Rittal 2025