

Rittal – The System.

Faster – better – everywhere.



SK 3286.850

Shallow air duct system

State: 2026-07-02 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SK 3286.850 - Shallow air duct system for roof-mounted cooling units and roof-mounted air-water heat exchangers

Cold air can be routed directly to specific areas of the enclosure using the air duct system. This eliminates the risk of air short circuits due to self-ventilated installed devices. The shallow ducts can be cut to the desired length.

Features

| | |
|---------------------|--|
| Model No. | SK 3286.850 |
| Product description | Cold air can be routed directly to specific areas of the enclosure using the air duct system. This eliminates the risk of air short circuits due to self-ventilated installed devices. The dimensions of the shallow duct are W x H x D 229 x 1500 x 29 mm, and can be shortened to the required length. |
| Applications | Suitable for enclosures with widths of 800 mm or more and depths of 600 mm or more. |
| Material | Flame-resistant plastic to DIN 4102/B1 |
| Color | RAL 7035 |
| Supply includes | Flat duct Adaptor Compensating piece Deflector, 90° |
| Mounting tip | The air duct adapter 3286.840 is required for installation with devices 3359.XXX and 3382.XXX. |
| Note | Do not direct cold air straight at active components. When using the ducting system, the performance of the cooling unit may be reduced, depending on the application in question. Cannot be used in conjunction with quick-change frames. |

Features

| | |
|------------------------|--|
| Suitable for Model No. | 3209.... 3210.... 3273.... 3383.... 3384.... 3385.... 3359.... 3382.... |
| Packaging unit | 1 pc(s). |
| Net weight | 2.3 kg |
| Gross weight | 2.46 kg |
| Customs tariff number | 39269097 |
| ETIM 9 | EC011217 |
| ETIM 8 | EC011217 |
| ECLASS 8.0 | 22410601 |
| Product description | SK Air duct system Flat, for SK 3209/3210/3273/3383/3384/3385/3359/3382, WHD: 229 x 1500 x 29 mm |