Rittal – The System.

Faster - better - everywhere.





SK 3286.970 Air duct system

State: 2025-11-18 (Source: rittal.com/ca-en)



SK 3286.970 - Air duct system for roof-mounted cooling units and roof-mounted air-water heat exchangers

Cold air can be routed directly to specific areas of the enclosure using the air duct system. This eliminates the risk of air short circuits due to self-ventilated installed devices. The shallow ducts can be cut to the desired length.

Features

Model No.	SK 3286.970			
Product description	Cold air can be routed directly to specific areas of the enclosure using the air duct system. This eliminates the risk of air short circuits due to self-ventilated installed devices. The dimensions of the shallow duct are W x H x D 229 x 1500 x 29 mm, and can be shortened to the required length.			
Material	Flame-resistant plastic to DIN 4102/B1			
Color	RAL 7035			
Supply includes	Flat duct Compensating hose (length approx. 1 m)			
Note	Do not direct cold air straight at active components. When using the ducting system, the performance of the cooling unimay be reduced, depending on the application in question. For devices 3359/3382, the air duct adapter 3286.840 is additionally required.			
Suitable for Model No.	3386 3387			
Packaging unit	1 pc(s).			
Net weight	2.9			
Gross weight	3			
Customs tariff number	39269097			
EAN	4028177325456			
ETIM 9	EC011444			

© Rittal 2025 2

Features

ETIM 8	EC011444
ECLASS 8.0	22410601

Approvals

Certificates EAC	Certificates	EAC		
------------------	--------------	-----	--	--

© Rittal 2025 3