

Rittal – The System.

Faster – better – everywhere.



SK 3363.100

Air-Water Heat Exchangers

State: 2025-07-11 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SK 3363.100 - Air-Water Heat Exchangers wall-mounted

Output categories 1023.64 - 17060.71 BTU/h. For use in tough environments. Convenient mounting options and flexible water connection options. External mounting or full internal mounting possible.



Features

| | |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model No. | SK 3363.100 |
| Version | wall-mounted Water-carrying parts copper/brass (Cu/CuZn) |
| Product description | To be used in rough environments and temperature ranges of up to +70 °C. Convenient assembly options and flexible water connection options. Partial or full internal mounting possible. |
| Color | RAL 7035 |
| Supply includes | Wired ready for connection Drilling template Sealing and assembly components |
| Total cooling output | L 35 W 10 at 400 l/h: 0.5 kW |
| Rated operating voltage | 230 V, 1~, 50 Hz/60 Hz |
| Rated power Pel | At 50 Hz: 37 W At 60 Hz: 38 W |
| Rated current max. | At 50 Hz: 0.18 A At 60 Hz: 0.18 A |

Features

| | |
|------------------------------------------|-----------------------------------------------------------------|
| Permissible operating pressure (p. max.) | 1 - 10 bar |
| Type of connection (electrical) | Plug-in terminal strip |
| Duty cycle | 100 % |
| Cooling medium | Water (see Internet for specifications) |
| Water inlet temperature | 1 °C...30 °C |
| Water connections | ½" connector sleeve G ¾" external thread |
| Temperature control | Basic controller (factory setting +35 °C) |
| Operating temperature range | 1 °C...70 °C |
| Note | Integral non-return valve for version with e-Comfort controller |
| Dimensions | Width: 280 mm Height: 550 mm Depth: 120 mm |
| Pre-fuse | Miniature circuit-breaker/fuse: 4 A |
| Setting range | 20 °C...55 °C |
| Protection category IP to EN 60 529 | IP 55 IP 65 available on request |
| Protection category NEMA | UL Type 1 UL Type 3R UL Type 12 |
| Packaging unit | 1 pc(s). |
| Net weight | 8.896 |
| Gross weight | 9.364 |
| Customs tariff number | 84158300 |
| EAN | 4028177495630 |
| ETIM 9 | EC002515 |
| ETIM 8 | EC002515 |
| ECLASS 8.0 | 27180712 |

Approvals

Approvals

CSA

30 - KC Korea

UL + C-UL - FTTA

UR + C-UR (recognized)

Explanations

Declaration of conformity