

# Rittal – The System.

Faster – better – everywhere.



## AS 4051.232

## Wire rail WT

State: 2026-02-06 (Source: [ittal.com/ca-en](https://www.ittal.com/ca-en))

# AS 4051.232 - Wire rail WT

The ready-cabled wires are fed to the WT 28 wire rail with a cross-section of 0.75 mm<sup>2</sup> by removal handling.



## Features

Model No.	AS 4051.232
Benefits	<p>Project-related commissioning for downstream processes</p> <p>Project-related sorting of wires</p> <p>Optimal removal handling</p> <p>Rail system prepared for optimal workplace picking</p> <p>No wire sorting required</p> <p>Simplifies wiring process with step-by-step instructions in Eplan Smart Wiring</p> <p>Optimal in combination with the Wire Cart for perfect workstation commissioning</p>
Supply includes	Wire rail WT 28
Note	The gap dimension indicates the maximum diameter of the wire insulation.
Suitable for Model No.	4051.205 4051.210 4051.024 4051.036
Applications	For single wires with cross-section 0.75 mm <sup>2</sup> (clearance 2.8 mm)
Packaging unit	1 pc(s).
Net weight	0.8
Gross weight	0.834
Customs tariff number	76169990

# Features

---

EAN

4028177981096