

Rittal – The System.

Faster – better – everywhere.



AS 4051.232 Wire rail WT

State: 2025-09-15 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AS 4051.232 - Wire rail WT

The ready-cabled wires are fed to the WT 28 wire rail with a cross-section of 0.75 mm² by removal handling.



Features

Model No.	AS 4051.232
Benefits	Project-related commissioning for downstream processes Project-related sorting of wires Optimal removal handling Rail system prepared for optimal workplace picking No wire sorting required Simplifies wiring process with step-by-step instructions in Eplan Smart Wiring Optimal in combination with the Wire Cart for perfect workstation commissioning
Supply includes	Wire rail WT 28
Note	The gap dimension indicates the maximum diameter of the wire insulation.
Suitable for Model No.	4051.205 4051.210 4051.024 4051.036
Applications	For single wires with cross-section 0.75 mm ² (clearance 2.8 mm)
Packaging unit	1 pc(s).
Net weight	0.8
Gross weight	0.834
Customs tariff number	76169990

Features

EAN	4028177981096
-----	---------------