Rittal – The System.

Faster – better – everywhere.





AS 4051.232 Wire rail WT

State: 2025-12-16 (Source: rittal.com/ca-en)



AS 4051.232 - Wire rail WT

The ready-cabled wires are fed to the WT 28 wire rail with a cross-section of 0.75 mm² by removal handling.





Features

| Model No. | AS 4051.232 |
|------------------------|---|
| Benefits | Project-related commissioning for downstream processes Project-related sorting of wires |
| | Optimal removal handling |
| | Rail system prepared for optimal workplace picking |
| | No wire sorting required |
| | Simplifies wiring process with step-by-step instructions in Eplan Smart Wiring |
| | Optimal in combination with the Wire Cart for perfect workstation commissioning |
| Supply includes | Wire rail WT 28 |
| Note | The gap dimension indicates the maximum diameter of the wire |
| | insulation. |
| Suitable for Model No. | 4051.205 |
| | 4051.210 |
| | 4051.024 |
| | 4051.036 |
| Applications | For single wires with cross-section 0.75 mm² (clearance 2.8 mm) |
| Packaging unit | 1 pc(s). |
| Net weight | 0.8 |
| Gross weight | 0.834 |
| Customs tariff number | 76169990 |
| | |

© Rittal 2025

Features

EAN

4028177981096

© Rittal 2025 3