Rittal – The System.

Faster – better – everywhere.





AS 4051.237 Wire rail WT

State: 2025-07-11 (Source: rittal.com/ca-en)

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP

ENCLOSURES

AS 4051.237 - Wire rail WT

The ready-cabled wires are fed to the WT 53 wire rail with a cross-section of 6.0 mm² by removal handling.



Features

Model No.	AS 4051.237
Product description	Busbar tightener for Perforex machining center BC and Perforex Milling Terminal MT, for easy processing of copper bars. Suitable for drilling and tapping.
Benefits	Project-related commissioning for downstream processes
	Project-related sorting of wires
	Optimal removal handling
	Rail system prepared for optimal workplace picking
	No wire sorting required
	Simplifies wiring process with step-by-step instructions in Eplan
	Smart Wiring
	Optimal in combination with the Wire Cart for perfect workstation
	commissioning
Supply includes	Wire rail WT 53
Note	The gap dimension indicates the maximum diameter of the wire
	insulation.
Suitable for Model No.	4051.205
	4051.210
	4051.024
	4051.036
Applications	For single wires with cross-section 6 mm ² (clearance 5.3 mm)
Packaging unit	1 pc(s).

Features

Net weight	0.85
Gross weight	1
Customs tariff number	76169990
EAN	4028177981041