


Rittal – The System.

Faster – better – everywhere.



AS 4055.322

Hole punch, square

State: 2025-09-07 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AS 4055.322 - Hole punch, square for carbon steel

For punching square cut-outs

Features

Model No.	AS 4055.322
Product description	For punching square cut-outs. The hole punch is operated with a hydraulic punch.
Benefits	With side chute for waste No jamming of die
Supply includes	Die Stamp Tension bolts Lock nut Plastic case Thrust nut with ball bearing Adapter for hydraulics
Workable material	Carbon steel
Max. material thickness that can be machined for sheet steel	2 mm
Hydraulic operation	Yes
Manual operation	Yes
□ hole punch	22.2 x 22.2 mm
Dimensions	Width: 22.2 mm
Packaging unit	1 pc(s).
Net weight	0.7
Gross weight	0.738
Customs tariff number	82073010
EAN	4028177808393
ETIM 9	EC000156
ETIM 8	EC000156

Features

ECLASS 8.0

21049047