

Rittal – The System.

Faster – better – everywhere.



AS 4055.480

Hole punch set, metric

State: 2025-08-21 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AS 4055.480 - Hole punch set, metric for carbon steel

For punching round cut-outs

Features

Model No.	AS 4055.480
Version	With 3 cutting tips
Product description	For punching round cut-outs. The hole punch is operated with a wrench or hydraulic punch.
Supply includes	5 dies 5 stamps Plastic case
Workable material	Carbon steel
Max. material thickness that can be machined for sheet steel	2 mm 2 mm 2 mm 2 mm 3 mm
Ø hole punch	16.2 mm 20.4 mm 25.4 mm 32.5 mm 40.5 mm
For thread	M16 M20 M25 M32 M40
Note	Tension screws with a ball bearing must be used when operating with a wrench

Features

Suitable for hydraulic bolt order number	4055.661
	4055.661
	4055.661
	4055.661
	4055.663
Packaging unit	1 pc(s).
Net weight	0.95
Gross weight	0.98
Customs tariff number	82073010
EAN	4028177808607
ETIM 9	EC002121
ETIM 8	EC002121
ECLASS 8.0	21049047