## Rittal – The System.

Faster – better – everywhere.





# TS 4166.000 Captive nut

State: 2025-11-19 (Source: rittal.com/ca-en)



## TS 4166.000 - Captive nut

Used on enclosures and rails with rectangular  $12.5 \times 10.5 \text{ mm}$  system punching with compression spring as an insertion aid to ensure reliable mechanical and electrical connection in the system punchings.



#### **Features**

Model No.	TS 4166.000	
Product description	The compression spring designed as an insertion aid ensures reliable mechanical and electrical connection in the hole profile.	
Installation options	On the vertical TS, VX SE enclosure section via adapter rail for VX compatibility	
	On the horizontal TS enclosure section	
	On the horizontal VX SE enclosure section, bottom	
	On the horizontal VX SE enclosure section top, in depth	
	On punched rails 23 x 23 mm	
	On mounting chassis 23 x 73 mm	
	On mounting chassis 45 x 88 mm	
	On 23 x 73 mm system chassis	
	On enclosures and rails with rectangular hole profile 12.5 x 10.5 mm	
Dimensions	Thread: M5	
Thread	M5	
Packaging unit	50 pc(s).	
Net weight	0.4	
Gross weight	0.474	
Customs tariff number	73181692	
EAN	4028177641815	

© Rittal 2025

### **Features**

ETIM 9	EC002358	
ETIM 8	EC002358	
ECLASS 8.0	23110815	

© Rittal 2025 3