Rittal – The System.

Faster – better – everywhere.



SZ 4176.000

Punched Rails, 23 x 23 mm

State: 2026-02-10 (Source: rittal.com/ca-en)

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

SZ 4176.000 - Punched Rails, 23 x 23 mm for VX, TS, VX SE

Mounted on the horizontal and vertical enclosure sections using additional assembly components.

Features

Model No.	SZ 4176.000
Material	Carbon steel
Surface finish	Zinc-plated
Length	1,695 mm
Installation options	On the vertical enclosure section: Directly via support brackets TS, via adapter rail for PS compatibility in conjunction with angle brackets, mounting brackets or support brackets PS. On the horizontal enclosure section: Directly via angle brackets, mounting brackets or support brackets PS
Suitable for	Enclosure type: VX TS VX SE Suitable for width or height or depth: 1,800 mm
Packaging unit	6 pc(s).
Net weight	6.318
Gross weight	6.65
PCF/VE (cradle-to-gate)	25.3 kg CO2 eq (Cat B)

Features

Information regarding the PCF class	Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared
Customs tariff number	73269098
EAN	4028177093249
ETIM 9	EC002620
ETIM 8	EC002620
ECLASS 8.0	27189234