


Rittal – The System.

Faster – better – everywhere.



SZ 4176.000

Punched Rails, 23 x 23 mm

State: 2026-02-10 (Source: [ittal.com/ca-en](https://www.ittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SZ 4176.000 - Punched Rails, 23 x 23 mm for VX, TS, VX SE

Mounted on the horizontal and vertical enclosure sections using additional assembly components.



Features

| | |
|-------------------------|--|
| Model No. | SZ 4176.000 |
| Material | Carbon steel |
| Surface finish | Zinc-plated |
| Length | 1,695 mm |
| Installation options | On the vertical enclosure section: Directly via support brackets TS, via adapter rail for PS compatibility in conjunction with angle brackets, mounting brackets or support brackets PS. On the horizontal enclosure section: Directly via angle brackets, mounting brackets or support brackets PS |
| Suitable for | Enclosure type: VX TS VX SE Suitable for width or height or depth: 1,800 mm |
| Packaging unit | 6 pc(s). |
| Net weight | 6.318 |
| Gross weight | 6.65 |
| PCF/VE (cradle-to-gate) | 25.3 kg CO ₂ eq (Cat B) |

Features

| | |
|-------------------------------------|--|
| Information regarding the PCF class | Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared |
| Customs tariff number | 73269098 |
| EAN | 4028177093249 |
| ETIM 9 | EC002620 |
| ETIM 8 | EC002620 |
| ECLASS 8.0 | 27189234 |