

# Rittal – The System.

Faster – better – everywhere.



## DK 5302.200

## Blanking panel, 19" ( 482.6 mm)

State: 2026-05-22 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# DK 5302.200 - Blanking panel, 19" ( 482.6 mm) Tool-free attachment

Allows for a quick and tool-free closure, as well as the thermal separation of unpopulated mounting surfaces in the 19" 1 U grid dimension.

## Features

Model No.	DK 5302.200
Benefits	Larger areas may be covered by combining multiple units. Versatile panel for individual requirements. Can be expanded on both sides with additional panels. Repeated removal and re-use possible
Material	Plastic Fire behavior according to UL 94 HB, halogen-free
Surface finish	Matte
Color	RAL 9005
Supply includes	Blanking panel, 1 U, with integral quick-fastening
Build-up height	1 U
Dimensions	Width: 482.6 mm
Height units	1 U
Packaging unit	5 pc(s).
Net weight	0.4 kg
Gross weight	0.605 kg
PCF/VE (cradle-to-gate)	1.99 KG CO2e
Customs tariff number	73269098
ETIM 9	EC000456
ECLASS 8.0	27189217
Product description	Blanking panel, 482.6 mm (19"), 1 U, tool-free attachment, plastic, RAL 9005