
Rittal - The System.

Faster – better – everywhere.





DK 5514.120 TS IT Network/Server Enclosure

State: 2025-11-07 (Source: rittal.com/ca-en)



DK 5514.120 - TS IT Network/Server Enclosure with glazed door, with 19" profile rails

TS IT is sealed for direct enclosure-specific climate control. 482.6 mm (19") interior installation with depth-variable 482.6 mm (19") profile rails for a load capacity of up to 1,500 kg, available in a range of size variants.



Features

Model No.	DK 5514.120
Material	Carbon steel
	Aluminum
	Viewing door: Single-pane safety glass, 3 mm
Surface finish	Enclosure frame: Dipcoat-primed
	Interior installation: Dipcoat-primed
	Doors and roof: Dipcoat-primed, powder coated
General color	RAL 7035
Color	Housing frame and panels: RAL 7035
	Interior installation: RAL 9005

© Rittal 2025 2

Features

	5 1 6 T00 W 1 6 1 6 1 6
Supply includes	Enclosure frame TS 8 with doors and roof plate Glazed aluminum door, front, 180° hinges
	Lock front and rear: Comfort handle for semi-cylinders and security
	lock 3524 E
	Two 482.6 mm (19") mounting sections front and rear, variably
	mounted on support strips with quick-release fasteners
	Spacers, height 50 mm, for raising the cover plate above the fan
	breakout in the roof panel, for passive ventilation (enclosed) Not required for variants without cutout.
	Connection accessories for potential equalization with earthing point (supplied loose)
	12 x 19" fasteners 1 U, contacting (supplied)
	50 multi-tooth screws, conductive (supplied loose) IPPC pallet
	Roof plate, multi-piece, removable, with side cable entry in the depth
	and covered cut-out for fan mounting plate
	Carob steel door rear, closed, vertically divided, 180° hinges
Dimensions	Width: 800 mm
	Height: 2,200 mm
	Depth: 1,000 mm
Height units	47 U
Height units	47 U
Mounting space to 19" level, front/rear	87 mm / 165 mm
Distance between levels as delivered	745 mm
Design doors	Solid
Design of 19" mounting level(s)	Profile rails, 482.6 mm (19")
Load capacity	15,000 N
Note	The door-opening angle may vary depending on site requirements or applications
Base material	Carbon steel
Packaging unit	1 pc(s).
Net weight	114.2

© Rittal 2025 3

Features

Gross weight	120.2
EAN	4028177703346
E-Number Sweden	E7239848
ETIM 9	EC002499
ECLASS 8.0	27180207

Approvals

Approvals	UL + C-UL (listed)
Certificates	Surface finish
Explanations	Declaration of conformity

© Rittal 2025